



# SS 250 / 500

## DATASHEET

The SS (250-500) Series provides the production of pure water needed for solar panel cleaning. It produces pure water by reverse osmosis. It obtains pure water by taking mains or well water and passing it through physical filter, membrane and sedimentation filter respectively.



*Since the product information, descriptions and images in this document are used for promotional purposes, Robsys reserves the right to make changes and innovations in the information, descriptions and visual changes of the products without prior notice.*



MECHANICAL FEATURES		
Model	SS 250	SS 500
Dimension (width*length*height)	576 x 542 x 1355 (mm)	576 x 542 x 1355 (mm)
Weight	54 kg	74 kg

POWER SUPPLY FEATURES	
Voltage	220
Frequency	50 Hz

PURE WATER SYSTEM FEATURES		
Pure Water Production Capacity	250 L	500 L
Water Inlet Pressure	4 Bar	6 Bar
Filter System	Coarse Sediment Filter + Automatic Valve Carbon Filter + Sedimentation Filter + Reverse Osmosis (RO) Membrane Filters	
Main Membrane Filter	RO Membrane Filter H/250 L	
Number of Main Membrane Filters	1	2
Water Output Values	0-20 Microsiemens	
Optional Elements	Thermoplastic or Pneumatic Water Pipe; Power Cord	
Operating Temperature	min 1 °C ; max +60 °C	

### MECHANICAL DIMENSIONS

