

# TILTING CONTAINERS TYPE EXPO®



## Compact, roll forward mechanism

- optimised load centre
- can be emptied at any height by cable operated from the driver's seat
- body with all-round reinforced edging
- sturdy frame with fork sleeves
- can be secured to prevent slipping and unintentional emptying
- wheels can be fitted later

## Accessories

- EXPO 150-275: 2 swivel + 2 fixed polyamide castors Ø 100 mm, one swivel castor with brake - construction height 125 mm
- EXPO 300-2100: 2 swivel + 2 fixed polyamide castors Ø 180 mm, one swivel castor with brake - construction height 225 mm
- galvanized lid, can be opened from both sides
- welding, oil and watertight
- trailer coupling and towing bar



EXPO with castors



EXPO with lid




EXPO 150-275: ideal for use under machines as the dumping edge is only 445 mm high



EXPO with lid

	Volume approx. (m <sup>3</sup> )	Dimensions (l x w x h) in mm	Load capacity in kg	Weight in kg paint. / galv.
EXPO 150	0,15	960 x 640 x 540	750	70 / 76
EXPO 225	0,225	960 x 925 x 540	750	78 / 84
EXPO 275	0,275	960 x 1210 x 540	750	86 / 93
EXPO 300	0,30	1260 x 770 x 835	750	112 / 121
EXPO 600	0,60	1260 x 1070 x 835	1000	131 / 141
EXPO 900	0,90	1260 x 1570 x 835	1000	165 / 178
EXPO 1200	1,20	1720 x 1070 x 1095	1500	200 / 215
EXPO 1700	1,70	1720 x 1570 x 1095	1500	240 / 258
EXPO 2100	2,10	1720 x 1870 x 1095	1500	265 / 285

	Fork sleeve inside dimensions in mm		
	A	B	C
EXPO 150-275	170	200	80
EXPO 300	300	200	80
EXPO 600-2100	600	200	80



Finish:

RAL 2000

RAL 3000

RAL 5012

RAL 6011

RAL 7005

hot-dip galvanized