



ETX easy tool exchange



Special wheels for grinding free of streaks

## DSM 800S – For large areas

The right answer for professional grinding of large areas on time. The DSM 800 proves itself by the powerful drive system and high grinding performance also under heavy working conditions.

### Applications

Suited for coating removal, grinding and polishing of concrete, industrial- and natural stone floors.

### Features

- DIF- Diamond Floating Device = less vibration
- Adjustable grinding pressure (optional)
- Ergonomic handle design
- ETX-Easy-Tool-Exchange
- Robust in design
- Power indicator

## DSM 800S



Technical data		DSM 800S
Voltage	V	400
Frequency	Hz	50
Power output	kW	15
Ø – working width	mm	800
Ø – grinding disc	mm	3 x 270
Grinding pressure	kg	207/245/314
Weight	kg	506
Working to the edge	mm	10
Tool speed	r.p.m.	400–1200
Tank	l	26
Ø – suction outlet	mm	76
Ref. No.		716003

## » DSM 250 – 400 – 450 – 530 – 530S – 650S – 650RC – 800S – 800RC

Machine	Volt/Hz	Power output kW	Speed (min <sup>-1</sup> )	Weight kg	Power indicator Plug	Ref.	€/piece
DSM 250	230/50	2,2	1450	57	16A,EU	713500	2.666,00 €
DSM 250	400/50	2,2	1450	57	16A,EU	713525	2.839,00 €
DSM 250	220/60	1,5	1450	56	16A,EU	713526	3.639,00 €
DSM 400	230/50	2,2	600	75	16A,EU	728001	4.228,00 €
DSM 400	400/50	4,0	900	109	16A,EU	728000	7.084,00 €
DSM 400	220/60	1,5	600	74	16A,EU	728006	5.619,00 €
DSM 450	230/50	2,2	400–1200	103	16A,EU	719000	☎
DSM 450P	400/50	2,2	400	118	16A,EU	719010	☎
DSM 450E	400/50	2,2	1200	118	16A,EU	719001	☎
DSM 530	3 x 400/50	4,0	400–1200	152	16A,EU	715500	☎
DSM 530S	3 x 400/50	7,5	400–1200	238	16A,EU	711502	☎
DSM 650S	3 x 400/50	11	400–1200	310–360	32A,EU	712006	☎
DSM 800S	3 x 400/50	15	400–1200	430–480	32A,EU	716003	☎
DSM 650RC	3 x 400/50	11	400–1200	615	32A,EU	729000	
DSM 800RC	3 x 400/50	15	400–1200	615	32A,EU	716500	