



**High Performance**

**V2 POWER INOX to work on stainless steel** Ordering example: A27441150401445

**Packing unit:**  
10 pcs. per type  
V<sub>max</sub>: 60 m/s  
Z POWER – Abrasive cloth using Zirconia Alum. Oxide with special coating containing active grinding additives

**Series**



Description	Grits	D mm	H mm	n <sub>max</sub> (V/min)	Product-Number	recommended for
V2 POWER 115	Z Power 40	115	22,23	13.300	A27441150401445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 115	Z Power 60	115	22,23	13.300	A27441150601445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	Z Power 40	125	22,23	12.200	A27441250401445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	Z Power 60	125	22,23	12.200	A27441250601445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	Z Power 40	178	22,23	8.500	A27441780401445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	Z Power 60	178	22,23	8.500	A27441780601445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

**Properties:**

- no glazing or heat generation
- equally efficient for both edge and surface applications
- iron-sulphur-chlorine free

**High Performance**

**V2 POWER Heavy Duty for roughest application** Ordering example: A27441150401450

**Packing unit:**  
10 pcs. per type  
V<sub>max</sub>: 60 m/s  
Ceramic – ceramic grain

**Series**

Description	Grits	D mm	H mm	n <sub>max</sub> (V/min)	Product-Number	recommended for
V2 POWER 115	Ceramic 40	115	22,23	13.300	A27441150401450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 115	Ceramic 60	115	22,23	13.300	A27441150601450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	Ceramic 40	125	22,23	12.200	A27441250401450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	Ceramic 60	125	22,23	12.200	A27441250601450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	Ceramic 40	178	22,23	8.500	A27441780401450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	Ceramic 60	178	22,23	8.500	A27441780601450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 230	Ceramic 40	230	22,23	6.600	A27442300401428	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

**Properties:**



- particularly robust for edge grinding, on heat treated steels, surface scale or coated surfaces
- iron-sulphur-chlorine free

**>1000 W opt.**



**High Performance**

**V2 Power Steel for universal application on steel and aluminium** Ordering example: A27441000401465

**Packing unit:**  
10 pcs. per type  
V<sub>max</sub>: 60 m/s  
ZK – Abrasive cloth with Zirconia Alum. Oxide  
ZKS – Zirconia Alum. Oxide with special coating containing active grinding additives

**Series**



Description	Grits	D mm	H mm	n <sub>max</sub> (V/min)	Product-Number	recommended for
V2 POWER 100	ZK 40	100	16	15.300	A27441000401465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 100	ZK 60	100	16	15.300	A2744100601465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 115	ZK 40	115	22,23	13.300	A27441150401465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 115	ZK 60	115	22,23	13.300	A27441150601465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	ZK 40	125	22,23	12.200	A27441250401465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	ZK 60	125	22,23	12.200	A27441250601465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	ZK 40	178	22,23	8.500	A27441780401465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	ZK 60	178	22,23	8.500	A27441780601465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 230	ZKS 40	230	22,23	6.600	A27442300401418	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

**Properties:**

- tough grain with a high degree of resistance to pressure

**High Performance**

**V2 POWER ALU** Ordering example: A27441150401434

**Packing unit:**  
10 pcs. per type  
V<sub>max</sub>: 60 m/s  
SiC – Silicon carbide

**Series**

Description	Grits	D mm	H mm	n <sub>max</sub> (V/min)	Product-Number	recommended for
V2 POWER 115	SiC 36	115	22,23	13.300	A27441150361434	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 115	SiC 40	115	22,23	13.300	A27441150401434	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	SiC 36	125	22,23	12.200	A27441250361434	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	SiC 40	125	22,23	12.200	A27441250401434	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	SiC 24	178	22,23	8.500	A27441780241434	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	SiC 36	178	22,23	8.500	A27441780361434	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

**Properties:**

- silicon carbide (SiC) ideally suited for preparation and finishing of weld seams with various aluminium alloys
- Silicon carbide (SiC) ideally suited for the machining of contemporary workpiece materials such as CFRP or GRP

