


280 Flap Wheels of abrasive cloth and abrasive fleece



Industry

LSL, Flap Wheels of abrasive cloth for angle grinder

Ordering example: A2280125200040



Packing unit:
5 pcs. per type
Vmax.: 80 m/s
NK = reg. Aluminium Oxide

Description	Grits	d ₁ mm	b mm	Thread	n _{recom.} (1/min)	n _{max.} (1/min)	Product-Number	recommended for
LSL 125020	NK 40	125	20	M14	9.600	12.200	A2280125200040	1 2 3 4 5 6 7 8
NEW LSL 125020	NK 40	125	20	5/8"	9.600	12.200	A2280125200040001	1 2 3 4 5 6 7 8
LSL 125020	NK 60	125	20	M14	9.600	12.200	A2280125200060	1 2 3 4 5 6 7 8
NEW LSL 125020	NK 60	125	20	5/8"	9.600	12.200	A2280125200060001	1 2 3 4 5 6 7 8
LSL 125020	NK 90	125	20	M14	9.600	12.200	A2280125200080	1 2 3 4 5 6 7 8
NEW LSL 125020	NK 90	125	20	5/8"	9.600	12.200	A2280125200080001	1 2 3 4 5 6 7 8
LSL 125020	NK 120	125	20	M14	9.600	12.200	A2280125200120	1 2 3 4 5 6 7 8
NEW LSL 125020	NK 120	125	20	5/8"	9.600	12.200	A2280125200120001	1 2 3 4 5 6 7 8

Advantages:

- Fits onto standard angle grinders
- Replaces the use of shaft mounted flap wheels (where no straight grinder is available)
- No flange needed
- Ideal for welding seams on Stainless Steel (tanks)

Application examples:

- De-rusting, removal of surface coatings and oxidise layers
- Cleaning of welding seams
- Grinding in the tank industry
- Grinding in the assembling industry

Application info:


Only to be used on the periphery of the wheel



Industry

LSV, Grinding wheels of abrasive fleece, tailor-made solution

Ordering example: LSV 100050 A 104 W Bore 13



Packing unit:
Minimum ordering quantity 25 pcs. per type
Vmax.: 35 m/s
Other dimensions, bores or qualities, e.g. "very hard" or "Poly Urethane-foamed" are available on request. Possible diameters 90 mm to max. 400 mm.
A = reg. Aluminium Oxide
C = Silicon Carbide

Description	Grits	Quality	d ₁ mm	b mm	Bore d ₂	recess on both sides	recess on both sides	n _{recom.} (1/min)	n _{max.} (1/min)	recommended for
-------------	-------	---------	----------------------	---------	------------------------	-------------------------	-------------------------	--------------------------------	------------------------------	-----------------

Find (1/2) X

A2280125200060 ⚙️

Previous
Next


Flap Wheels of abrasive fleece 281



Industry

LSV, Grinding wheels of abrasive fleece, tailor-made solution

Ordering example: LSV 100050 A 104 M Bore 13



Packing unit:
Minimum ordering quantity 25 pcs. per type
Vmax.: 35 m/s
Other dimensions, bores or qualities, e.g. "very hard" or "Poly Urethane-foamed" are available on request. Possible diameters 90 mm to max. 400 mm.
A = reg. Aluminium Oxide
C = Silicon carbide

Description	Grits	Quality	d ₁ mm	b mm	Bore d ₂ mm	recess on both sides d ₄ mm	recess on both sides l ₂ mm	n _{recom.} (1/min)	n _{max.} (1/min)	recommended for
LSV 100050	A 104 M	medium	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	A 106 M	medium	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	A 107 M	medium	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	C 204 M	medium	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	C 206 M	medium	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	C 207 M	medium	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	A 104 H	hard	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	A 106 H	hard	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	A 107 H	hard	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	C 204 H	hard	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	C 206 H	hard	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 100050	C 207 H	hard	100	50	13-16-20	---	---	3.000	6.000	1 2 3 4 5 6 7 8
LSV 150050	A 104 W	soft	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	A 106 W	soft	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	A 107 W	soft	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	C 204 W	soft	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	C 206 W	soft	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	C 207 W	soft	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	A 104 M	medium	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	A 106 M	medium	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	A 107 M	medium	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	C 204 M	medium	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	C 206 M	medium	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	C 207 M	medium	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	A 104 H	hard	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	A 106 H	hard	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 150050	A 107 H	hard	150	50	13-16-20	47	18	2.000	4.000	1 2 3 4 5 6 7 8
LSV 160050	A 104 W	soft	160	50	13-16-20	47	18	1.900	3.800	1 2 3 4 5 6 7 8