

DSM 800S – For large areas and severe working conditions

The right solution for grinding and renovation of large areas. The DSM 800S impresses through a powerful drive and high grinding performance.



ETX easy tool exchange



Special wheels for grinding free of streaks

Applications

Grinding concrete, screed, industrial floors, asphalt, sticking of concrete, screed and asphalt, large-scale renovation, remove adhesives, coatings, fillers, regulate uneven floors, grinding and polishing concrete, screed, asphalt, natural stone, terrace

Technical data

Ref. No.		716003
Voltage	V	400
Frequency	Hz	50
Power output	kW	15
Working width	mm	800
No. of tools	mm	3 x 270
Grinding pressure, max.	kg	240/300/200
Operating weight	kg	510
Edge distance	mm	10
Tool speed	r.p.m.	400 - 1200
Tank	l	26
Ø-Dust control	mm	76
Tool mount		ETX1, ETX2, Velcro

Special characteristics

- ETX – Tool exchange
- DIF – Diamond floating device
- Ergonomical handle design
- MOP – Motor overload protection
- Counter rotating tools
- Grinding pressure, adjustable
- Speed control
- Tool turning direction
- Dead man switch
- Power indicator
- Robust in design

DSM 800S Accessories and tools, grinding from page 48, bush hammering from page 58