

Article: 20580-0105

## CABLE REEL ER3x1.5-15



20580-0105

**Luna** Manufactured in a heavy-duty design of impact resistant hardened plastic. Adapted for vehicle workshops and industry with demands on trouble free usage. Rewinders make the workplace safer without twisted cable coils that can cause tripping accidents and impair accessibility in the premises. Equipped with pivoted wall or roof bracket, which simplifies handling. The bracket can be pivoted approx. 300°. The cable lengths are controlled by a catch that comes into effect with each extended ½ metre and which can be disengaged if you want constant pulling. The cable is H0 5VV-F quality. Temperature range -5 °C to +40 °C.

1-phase has a thermal cut-out connected in the reel.

3-phase has a thermal cut-out in the reel, but is not connected and must be supplemented with an external connector, see the wiring diagram.

Supplied without connection cable.

Code no.	<u>20580-0105</u>	<u>20840-0101</u>	<u>20840-0200</u>
Short description	CABLE REEL ER3x1.5-15	CABLE REEL	CABLE REEL
Manufacturer's description	ECR3x1,5-15	ER3x2.5-22	ER5x2.5-17
Cable cross-section	3×1.5 mm <sup>2</sup>	3×2.5 mm <sup>2</sup>	5×2.5 mm <sup>2</sup>
Enclosure class	IP 42	IP 42	IP 42
Cable length	15 (14 + 1) m	22 (21+1) m	17 (16+1) m
Amperage	10 A	16 A	16 A
Max. load (wound)	1200 W	2000 W	2000 W
Max. load (fully unwound)	1800 W	3000 W	3000 W
Diameter	350 mm	550 mm	550 mm
Weight	4,2 kg	8 kg	9 kg
Thickness	175 mm	235 mm	235 mm
Qty/pack	1 PCS	1 PCS	1 PCS
Packaging	1 PCS	1 PCS	1 PCS