


LSL, Flap Wheels of abrasive cloth for angle grinder

Ordering example: A2280125200040

Packing unit:

5 pcs. per type

 v_{max} : 80 m/s

NK = reg. Aluminium Oxide

NEW: Also available with 5/8" thread on request.

Price on inquiry

| Description | Grits | d ₁ mm | b mm | Thread | n _{recom.} (1/min) | n _{max.} (1/min) | Product-Number | recommended for | |
|-------------|--------|----------------------|---------|--------|--------------------------------|------------------------------|----------------|-----------------|---|
| LSL 125020 | NK 40 | 125 | 20 | M14 | 9.600 | 12.200 | A2280125200040 | ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ | ■ |
| LSL 125020 | NK 60 | 125 | 20 | M14 | 9.600 | 12.200 | A2280125200060 | ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ | ■ |
| LSL 125020 | NK 80 | 125 | 20 | M14 | 9.600 | 12.200 | A2280125200080 | ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ | ■ |
| LSL 125020 | NK 120 | 125 | 20 | M14 | 9.600 | 12.200 | A2280125200120 | ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ | ■ |

Advantages:

- Fits onto standard angle grinders
- Replaces the use of shaft mounted flap wheels (where no straight grinder is available)
- No flange needed
- Ideal for welding seams on Stainless Steel (tanks)

Application examples:

- De-rusting, removal of surface coatings and oxidise layers
- Cleaning of welding seams
- Grinding in the tank industry
- Grinding in the assembling industry

Application info:

Only to be used on the periphery of the wheel

Material classification

- 1 STEELS AND CAST STEELS**
Rm up to 800 N/mm²
 - common structural steels
 - free cutting steels
 - case hardened steels
 - fine grained structural steels
 - extruded steels
 - toughened structural steels
 - boiler plate
 - nitrided steels
 - cast steels
 - heat treated steels
 - heat resistant structural steels
- 2 ALLOYED, TEMPERED STEELS**
Rm 800 up to 1200 N/mm²
 - case hardened steels
 - spring steels
 - fine grained structural steels
 - nitrided steels
 - heat treated steels
 - wear resistant steels
 - bearing steels
- 3 TOOL STEELS** Rm up to 1300 N/mm²
 - 60 - 65 HRC
 - high-speed steels
 - non-alloyed tool steels
 - cold working tool steels
 - hot working tool steels
- 4 RUST, ACID AND HEAT RESISTANT STEELS AND CAST STEELS**
 - austenitic
 - ferritic
 - ferritic-austenitic
 - heat-resistant
 - martensitic
 - stainless, sulphurized

- 5 CAST IRON**
- 6 ALUMINIUM, MAGNESIUM AND COPPER ALLOYS**
 - over 300 HB
 - 200-300 HB
 - up to 200 HB
 - over 15% Si
 - 10-15% Si
 - 0,5-10% Si
 - below 0,5% Si
- 7 TITANIUM AND NICKEL ALLOYS**
 - Rm 900 up to 1500 N/mm²
 - Rm up to 900 N/mm²
- 8 PLASTICS, WOOD, RUBBER**
- 9 GLASS / CARBIDES**
- 10 STONE / TILES / GAS CEMENT**
- 11 CONCRETE / REINFORCED CONCRETE**
- 12 CERAMIC / FLOOR TILES**
- 13 MARBLE**
- 14 GRANITE**
- 15 FRESHLY POURED CONCRETE**
- 16 ASPHALT**

- best suitable
- suitable
- delivery ex-stock
- ▲ delivery on request
- Ⓢ regrind service, please enquire

Safety Symbols

| | | | |
|--|---|---|---|
|  |  |  |  |
| Wear eye protection | Wear hearing protection | Wear a respirator | Read the instructions |
|  |  | | |
| Wear gloves | Only permitted with a back-up pad | | |
|  |  |  |  |
| Not permitted for wet grinding | Not permitted for face grinding | Do not use if damaged | Do not use for freehand cutting |