DSM 530S – Powerful grinder for demanding applications

The DSM 530S combines high grinding performance and user-friendly control. A powerful drive and robust design make it ideal for severe working conditions.



Applications

Grinding concrete, screed, industrial floors, asphalt, sticking of concrete, screed and asphalt, large-scale renovation, remove adhesives, coatings, fillers, regulate uneven floors, grinding and polishing concrete, screed, asphalt, natural stone, terrace

Technical data		
Ref. No.		711502
Voltage	V	400
Frequency	Hz	50
Power output	kW	7.5
Working width	mm	530
No. of tools	mm	3 x 230
Grinding pressure, max.	kg	165
Operating weight	kg	253
Edge distance	mm	10
Tool speed	r.p.m.	400 - 1200
Tank	I	15
Ø-Dust control	mm	76
Tool mount		ETX1, ETX2, Velcro

DSM 530S Accessories and tools, grinding from page 48, bush hammering from page 58



ADS: Anti-shock transmission



Special characteristics		
ETX – Tool exchange		
DIF – Diamond floating device		
Ergonomical handle design		
MOP – Motor overload protection		
Counter rotating tools		
Speed control		
Tool turning direction		
Dead man switch		
Power indicator		
For heavy duty work		
High grinding performance		
Easy to use		