

# DSM 250S

## DSM 250S – Subsurface preparation up to polishing

The new DSM 250S with pivoting grinding head for rimless grinding. The perfect addition to professional subsurface preparation and finishing of highly polished concrete and designer floors. Equipped with a water tank and continuous speed control for optimum wet grinding.



### Applications

Rimless grinding of concrete, screed, asphalt, regulate uneven floors, remove adhesives, fillers, regulate uneven floors, fine grinding of natural stone, cast stone, terrace

### Technical data

Ref. No.		713670
Voltage	V	230
Frequency	Hz	50
Power output	kW	2.2
Working width	mm	250
No. of tools	mm	250
Grinding pressure, max.	kg	25
Operating weight	kg	61
Edge distance	mm	0
Tool speed	r.p.m.	740 – 1500
Ø-Dust control	mm	50
Dimensions LxWxH	cm	100 x 40 x 100
Tool mount		ETX1, Velcro



Practical water tank for wet grinding



Abrasion-resistant wheels (streak-free) for clean working



Rimless grinding and polishing / pivoting grinding head

### Special characteristics

- Diamond floating device
- Swiveling grinding head left/right
- Stepless speed control from 740 -1500 r.p.m.
- Practical water tank for wet grinding
- Borderless grinding and polishing

DSM 250S Accessories and tools, grinding from page 48, milling from page 67