

# BE 200 ET 200 N

High capacity hoists – 200 kg

## BE 200 Standard Equipment

- ✓ Work positioning lever
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton pendant control, with emergency button and 16A IP67 EC flying plug
- ✓ Adjustable upper tie-rod
- ✓ Self-braking motor with magnetic device

## Optional Accessories

- ✓ Rigid frame
- ✓ Trolley with brake for the gantry

## Applications

Compact and lightweight, BE 200 can be transported and installed easily. Extremely versatile to install thanks to the variety of attachments available. The standard configuration envisages a bracket with an adjustable upper tie-rod.



## ET 200 N Standard Equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1.5 m pendant control
- ✓ Self-braking motor with magnetic device

## Applications

Ideal for operations that do not require bracket extension.



## Standard version

with adjustable upper tie-rod

		BE 200
Maximum capacity	kg	200
Av. full load lifting speed	m/min	20
Max. working height	m	30
Ø steel rope	mm	5
Rope length	m	31
Motor power rate 230V/50Hz	kW	0.75
Motor speed	rpm	1380
Running current	(A)	7.5
Machine weight	kg	30
SPL in operator's position	dB(A)	<74
Packing dimensions w/l/h	mm	250/820/350

## ET 200 N

Maximum capacity	kg	200
Av. full load lifting speed	m/min	19
Max. working height	m	30
Ø wire rope	mm	5
Rope length	m	31
Motor power rate 230V/50Hz	kW	0.75
Motor speed	rpm	1380
Running current	A	7.2
Machine weight	kg	42
SPL in operator's position	dB(A)	<70
Dimensions w/l/h	mm	330/770/520
Packing dimensions w/l/h	mm	350/820/500