


High Performance
SLTT INOX, our Turbo Flap Disc to work on stainless steel
Ordering example: A27201150400045



Packing unit:
 10 pcs. per type
 V_{max}: 80 m/s
 Z POWER – Abrasive cloth using Zirconia Alum. Oxide with special coating containing active grinding additives


Series

Description	Grits	D mm	H mm	n _{max} (1/min)	Product-Number	recommended for
SLTT 115	Z Power 40	115	22,23	13.300	A27201150400045	1 2 3 4 5 6 7 8
SLTT 115	Z Power 60	115	22,23	13.300	A27201150600045	1 2 3 4 5 6 7 8
SLTT 125	Z Power 40	125	22,23	12.200	A27201250400045	1 2 3 4 5 6 7 8
SLTT 125	Z Power 60	125	22,23	12.200	A27201250600045	1 2 3 4 5 6 7 8
SLTT 150	Z Power 40	150	22,23	10.200	A27201500400045	1 2 3 4 5 6 7 8
SLTT 178	Z Power 40	178	22,23	8.500	A27201780400045	1 2 3 4 5 6 7 8
SLTT 178	Z Power 60	178	22,23	8.500	A27201780600045	1 2 3 4 5 6 7 8

Eigenschaften:

- No glazing or heating of flaps, owing to top size coating
- equally efficient for both edge and surface applications
- iron-sulphur-chlorine free

High Performance
SLTT Heavy Duty, our Turbo Flap Disc for roughest application
Ordering example: A27201150400050



Packing unit:
 10 pcs. per type
 V_{max}: 80 m/s
 Ceramic – Abrasive cloth ceramic grain

Series


Description	Grits	D mm	H mm	n _{max} (1/min)	Product-Number	recommended for
SLTT 115	Ceramic 40	115	22,23	13.300	A27201150400050	1 2 3 4 5 6 7 8
SLTT 115	Ceramic 60	115	22,23	13.300	A27201150600050	1 2 3 4 5 6 7 8
SLTT 125	Ceramic 40	125	22,23	12.200	A27201250400050	1 2 3 4 5 6 7 8
SLTT 125	Ceramic 60	125	22,23	12.200	A27201250600050	1 2 3 4 5 6 7 8
SLTT 150	Ceramic 40	150	22,23	10.200	A27201500400050	1 2 3 4 5 6 7 8
SLTT 178	Ceramic 40	178	22,23	8.500	A27201780400050	1 2 3 4 5 6 7 8
SLTT 178	Ceramic 60	178	22,23	8.500	A27201780600050	1 2 3 4 5 6 7 8

Properties:

- particularly robust for edge grinding, on heat treated steels, surface scale or coated surfaces
- iron-sulphur-chlorine free

>1000 W opt.

High Performance
SLTT Steel, our Turbo Flap Disc for universal application on steel and aluminium
Ordering example: A27201150400065



Packing unit:
 10 pcs. per type
 V_{max}: 80 m/s
 ZK – Abrasive cloth with Zirconia Alum. Oxide

Series

Description	Grits	D mm	H mm	n _{max} (1/min)	Product-Number	recommended for
SLTT 115	ZK 40	115	22,23	13.300	A27201150400065	1 2 3 4 5 6 7 8
SLTT 115	ZK 60	115	22,23	13.300	A27201150600065	1 2 3 4 5 6 7 8
SLTT 125	ZK 40	125	22,23	12.200	A27201250400065	1 2 3 4 5 6 7 8
SLTT 125	ZK 60	125	22,23	12.200	A27201250600065	1 2 3 4 5 6 7 8
SLTT 150	ZK 40	150	22,23	10.200	A27201500400065	1 2 3 4 5 6 7 8
SLTT 150	ZK 60	150	22,23	10.200	A27201500600065	1 2 3 4 5 6 7 8
SLTT 178	ZK 40	178	22,23	8.500	A27201780400065	1 2 3 4 5 6 7 8
SLTT 178	ZK 60	178	22,23	8.500	A27201780600065	1 2 3 4 5 6 7 8

Properties:

- tough grain with a high degree of resistance to pressure
- quicker, more aggressive and longer tool life when compared with our current ZKS quality

