Decision support

Series/products	Application areas								Features and technical data																	
	Hotel and office cleaning	House and home	Garage / Workshop / Hobby	Outside area / coarse dirt	Cleaning large areas and buildings	Operational and machine cleaning	Wet-dry cleaning		Rubber wheels and castors	Noise insulated	Water level detection	Speed controller	Antistatically prepared	Accessory compartment	Brake (y/n)	Max. Power consumption/Watts	Vacuum (mbar, measured at the motor head)	Volume flow (l/s, measured at the motor head)	Max. Container volume/litres	Weight/kg	Reach (including cable and pipe)	Hose length and diameter	Sound volume dB (A)	Filter surface area cm²	Page
uClean																										
uClean 1420 HK		●	●				●		n	n	y	n	n	y	n	1400	259	69	20	7.8	9.75–10.75	1.75m / 35mm	72.5	3600	52
uClean 1432 HK		●	●				●		n	n	y	n	n	y	n	1400	259	69	32	8.1	9.75–10.75	1.75m / 35mm	72.5	3600	52
uClean 1432 ST			●	●		●	●		n	n	y	n	n	y	n	1400	259	69	32	8.1	9.75–10.75	1.75m / 49mm	72.5	3600	53
uClean LD-1420 HMT	●	●			●		●		y	y	y	2-level	n	y	y	1400	259	69	20	8.0	15.2–16.2	3.2m / 35mm	68.5	3600	54
uClean LD-1435 PZ					●	●	●		y	y	y	2-level	n	y	y	1400	259	69	35	9.9	15.2–16.2	3.2m / 35mm	68.5	3600	55
uClean LD-1445 Wet					●	●	●		j	j	j	2-level	n	j	n	1400	259	69	45	12,6	15,2–16,2	3.2m / 32mm	68,5	3600	57
eCRAFT																										
eCRAFT L 1422		●	●				●		n	n	j	n	n	j	n	1400	255	71	22	6,2	7.9–8,9	1.9m / 35mm	72	3600	58
eCRAFT PL 1422		●	●				●		n	n	j	n	n	j	n	1400	255	71	22	6,2	8.5–9,5	2.5m / 35mm	72	3600	58
GS																										
GS 2078 PZ					●	●	●		n	n	y	n	y	n	n	2400	205	108	78	23.5	11.7–12.7	3.5m / 40mm	77		60
GS 3078 PZ					●	●	●		n	n	y	n	y	n	n	3600	205	162	78	26.0	11.7–12.7	3.5m / 40mm	79		60
Special vacuum cleaners																										
uClean PA-1455 KFG FW							●		n	n	y	2-level	y	n	y	2200	248	61	55	22.0	18.0–50.0	2x 5m / 35mm	73	3600	63
uClean PA-1455 KFG							●		n	n	y	2-level	y	n	y	2200	248	61	55	20.3	18.0–50.0	5 & 10m / 35mm	73	3600	63

* for large volumes of liquid

CLEANING