

ROLLBETA - WHEELMAN II

Small-sized concrete mixers

Standard Equipment

- ✓ Single-phase 230V/50Hz or 115V/60Hz electric motor
- ✓ Gearmotor with steel and technopolymer gears
- ✓ Electric safety: built to EN 60204-1 double insulation norms, protected against spraying water (IP 55) and against overload and inadvertent starting again after a power failure.
- ✓ Packing: cardboard
- ✓ Available in the versions with steel drum and poly drum HDPE

Optional Accessories

- ✓ Rotating pivoting support

Applications

It is the lightweight, compact concrete mixer easy to transport, ideal for small building sites or refurbishment work. Its construction features make it suitable for professional use.

ROLLBETA WHEELMAN II

with STANDARD DOUBLE INSULATION



Rollbeta



Rollbeta with poly drum (HDPE)



Rollbeta rotating pivoting support (optional)

	ROLLBETA	WHEELMAN II
Drum capacity	l	134
Batch output	l	~100
Drum diameter	mm	610
Wheel dimensions	Ø mm	370x60
Electric power supply	V / Hz	230 / 50 Sph 230 / 60 Sph 110 / 50 Sph
Electric motor power rate	kW	0.3
Running current 230 V (110/115 V)	A	2.8 (6)
SPL in operator's position	dB(A)	63
Machine weight	kg	46
Machine dim. w/l/h	mm	660/1170/920
Packing dim. w/l/h	mm	660/730/700
Max stackability*		3 (h 2200 mm)

(*) Number of stackable pieces and total height including pallet