

MRO Sprayable Adhesive Tip Sheet

3M Industrial Adhesives and Tapes

Questions to Ask for Product Selection

- 1 What materials do you want to bond?
- 2 Do you require a structural or non-structural bond?
- 3 Are you willing to prepare the surfaces?
- What types of stresses will the bond be subjected to?
- 5 What types of environmental conditions will be involved?
- 6 Do you need repositioning time?
- What is the preferred bonding range?
- 8 What application method is appropriate for your production requirements?
- What is the present bonding or joining method?

78

Spray Adhesives

77

Multipurpose

3M[™] Super 77[™] Multipurpose Spray Adhesive

- High tack, high coverage and low soak-in formula
- Bonds many lightweight materials such as foils,
- carpeting, paper, cardboard, felt and more • Bonds in 15 seconds
- Bonds in 15 seconds

UPC Aerosol (Clear) 000-21200-96474-9, 6 oz. 000-76308-86234-3, 13.44 oz. 000-21200-21210-9, 16.75 oz. Cylinder (Clear) 000-5115-25776-6, Large Bulk (Clear) 000-21200-43793-9, 5 Gallon Pail 000-21200-43813-4, Open Head Steel Drum

Maintenance & Cleaning

3M[™] Adhesive Remover

Aerosol 000-21200-49048-4

UPC

- Removes adhesive without damaging the surface underneath
- 3M[™] Silicone Lubricant

Heavy Duty

3M[™] Hi-Strength 90

· Bonds to concrete,

and polyethylene

• High temperature and

Aerosol (Clear) 000-76308-86235-0, 12.23 oz. 000-21200-30023-3, 17.6 oz. 000-51111-07278-3, Inverted

Cylinder (Clear) 000-21200-41554-8, Large

000-51115-25774-2, Interme 000-51115-25775-9, Jumbo

Bulk (Clear) 000-21200-43797-7, 5 Gallon Pail 000-21200-43814-1, Open Head Steel Drum

moisture resistance

UPC

· High strength and fast-tack

adhesive performance

wood, MDF, laminates

90

Spray Adhesive

• Reliable lubricant can be used in a wide variety of applications

ediate

Fast drying to maintain productivityLong lasting and non-staining

to keep work surfaces clean

UPC Aerosol 000-21200-85822-2

3M[™] Foam Fast 74 Spray Adhesive • Fast-tacking adhesive with

Foam & Fabric

- soft, non-dimpling bond lines
- Immediate foam-tearing strength
- Ideal for bonding flexible urethane or latex foam to many substrates

UPC Aerosol (Clear) 000-5111-50045-9 Cylinder (Clear) 000-21200-49919-7, Large 000-5115-25741-4, Intermediate 000-5115-25742-1, Jumbo

Aerosol (Orange) 000-21200-82242-1 Cylinder (Orange) 000-21200-49158-0, Large 000-51111-18853-8, Intermediate 000-51111-18854-5, Jumbo

Specialty

3M[™] Polystyrene Insulation 78 Adhesive High solids adhesive formulated for expanded

- formulated for expanded polystyrene and foam insulations
- Bonds without cavitating foams
 Fast grabbing, fast drying formula

UPC Aerosol (Clear) 000-21200-41593-7 000-51111-07279-0, Inverted Bulk (Clear) 000-48011-53438-1, 5 Gallon Pail

3M[™] Rubber and Vinyl 80 Spray Adhesive

80

- High strength adhesive provides strong bonds for rubber and vinyl
 High temperature and
- Plasticizer resistant
- Fast-setting contact adhesive produces rapid results

UPC Aerosol (Yellow) 000-21200-82618-4

3M[™] Industrial Cleaner

Aerosol 000-21200-76394-6

UPC

 Removes grease, oil, ink and most adhesives without the need to soak

3M[™] 5-Way Penetrant

- Helps free rusted and frozen bolts, nuts and more
- Displaces moisture and "dries out" electronics
- Light-duty lubricant works well with delicate precision instruments

UPC Aerosol 000-21200-21305-2

Low VOC Spray Adhesives

Multipurpose

3M[™] Super 77[™] CA Multipurpose Spray Adhesive – Low VOC <25%*

 Bonds many lightweight materials such as foils, carpeting, paper, cardboard, felt and more

• Low soak-in and long open time

UPC Aerosol (Clear) 000-51111-97956-3



Maintenance & Cleaning

- 3M[™] Adhesive Remover Low VOC < 20%
- Removes grease, oil, ink and most adhesives without the need to soak or damaging the surface underneath
- Provides mold-release agents

UPC Aerosol 000-51111-97974-7 Reliable lubricant can be used in a wide variety of applications

3M[™] Silicone Spray

Low VOC 60%

- Fast drying to maintain productivity
- Long lasting and non-staining

UPC Aerosol 000-51111-07732-0

*Meets CARB/OTC VOC requirements and helps contribute to LEED® credits. Review applicable VOC requirements to ensure local compliance. **All products listed are GREENGUARD Gold Certified.

MRO Sprayable Adhesive Tip Sheet (cont.)

Mist Spray vs. Web Spray

Particle Spray

- Dispersions suspended particles that can settle (shake/purge)
- Translucent glue lines
- Non-telegraphing texture, smooth
- Fine, misty particle spray
- Particle sprays are odd number products (77, 27, 75...)

Lace Spray

- Solutions no particles, no settling (shake/purge not needed)
- Variable spray pattern
- Less overspray
- Lace, web spray pattern
- Lace sprays are even number products (90, 74, 72...)

Common Reasons for Bond Failure

- Insufficient pressure on bond
- Wrong adhesive or too thick of coating
- Too thin of coating
- Stress too great for that type of adhesive
- Bonds assembled while adhesive was still wet
- Lack of surface preparation
- Plasticizers attached and broke down adhesive

Value Story for 3M Aerosol Adhesives

- Ultimate convenience in a sprayable adhesive, no equipment, no mess, no set up time, minimal training, extremely portable
- Small jobs (doesn't mean small volume!), multiple stations, easy to use, precise placement of spray (lace) portability
- Compliments bulk or cylinder adhesives
- On job sites or away from spray booths

1. Use 3M[™] Multipurpose Adhesive when bonding fiberglass insulation to metal.



2. Use 3M[™] Heavy Duty Adhesive when bonding wood and laminate, lamination of large materials like wood, metal, plastic.



3. Use Specialty adhesive, 3M[™] Polystyrene 78 Spray adhesive when bonding polystyrene.



4. Use Maintenance and Cleaning, 3M[™] Adhesive Remover when removing adhesive residue.





Industrial Adhesives and Tapes Division 3M Center, Building 225-3S-06 St. Paul, MN 55144 USA

Phone 1-800-362-3550 Web 3M.com/sprayadhesives Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANNTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted.

3M and Super 77 are trademarks of 3M Company. LEED is a registered trademark of the United States Green Building Council (USGBC). Please recycle. © 3M 2018. All rights reserved. 78-9236-7809-4