



MONTO® Multipurpose rung ladder Tribilo®

Three-section aluminium multipurpose ladder usable as a leaning, extension and freestanding ladder with an extendable ladder section.

- + Powder-coated steel guiding profiles for greater ease of use
- + Self-locking levers (AutoSnap-System) for safe transport
- + Weather-resistant and tear-proof webbing straps as spread lock
- + Wide stabiliser for even greater stability
- + Slip-resistant foot caps and plugs (SafetyCap)

i The following ladders are suitable for use on stairs:
 Art.-No. 129741 – 3 x 8 rungs
 Art.-No. 129765 – 3 x 10 rungs
 Art.-No. 129789 – 3 x 12 rungs

i From size 3 x 12 rungs and above the removable ladder part can only be used with Trigon-Stabiliser.



Watch technic clip



| Number of rungs | | suitable for use on stairs | | | | | | | |
|--------------------------|--------------------|----------------------------|--------|--------|--------|--------|--------|--------|------|
| | | 3 x 9 | 3 x 10 | 3 x 12 | 3 x 14 | 3 x 8 | 3 x 10 | 3 x 12 | |
| 1 | | 6.85 | 7.65 | 9.30 | 10.90 | 6.05 | 7.65 | 9.30 | |
| | | 4.85 | 5.65 | 7.30 | 8.90 | 4.05 | 5.45 | 7.30 | |
| | | 6.05 | 6.90 | 8.60 | 10.25 | 5.25 | 6.90 | 8.60 | |
| | | 5.85 | 6.65 | 8.30 | 9.90 | 5.05 | 6.65 | 8.30 | |
| 2 | | 4.95 | 5.45 | 6.55 | 7.60 | 4.40 | 5.45 | 6.55 | |
| | | 2.95 | 3.45 | 4.45 | 5.60 | 2.40 | 3.45 | 4.45 | |
| | | 4.40 | 4.95 | 6.05 | 7.20 | 3.80 | 4.95 | 6.05 | |
| | | 4.20 | 4.70 | 5.70 | 6.90 | 3.65 | 4.70 | 5.70 | |
| 3 | | 3.85 | 4.10 | 4.65 | 5.20 | 3.60 | 4.10 | 4.65 | |
| | | 1.85 | 2.10 | 2.65 | 3.20 | 1.60 | 2.10 | 2.65 | |
| | | 2.70 | 3.00 | 3.55 | 4.10 | 2.40 | 3.00 | 3.55 | |
| | | 2.65 | 2.80 | 3.30 | 4.00 | 2.25 | 2.80 | 3.30 | |
| 4 | | 3.60 | 3.85 | 4.40 | 4.95 | 3.35 | 3.85 | 4.40 | |
| | | 1.60 | 1.85 | 2.40 | 2.95 | 1.35 | 1.85 | 2.40 | |
| | | 2.70 | 3.00 | 3.55 | 4.10 | 2.40 | 3.00 | 3.55 | |
| | | 2.60 | 2.85 | 3.40 | 4.00 | 2.35 | 2.85 | 3.40 | |
| 5 | | - | - | - | - | 4.40 | 4.95 | 5.45 | |
| | | - | - | - | - | 2.40 | 2.95 | 3.45 | |
| | | - | - | - | - | 3.25 | 3.80 | 4.35 | |
| | | - | - | - | - | 3.10 | 3.65 | 4.15 | |
| Stabiliser width approx. | | m | 1.00 | 1.15 | 1.25 | 1.25 | 0.90 | 1.15 | 1.25 |
| Product weight approx. | | kg | 16.7 | 18.3 | 27.3 | 31.3 | 15.3 | 18.3 | 27.3 |
| | Width (B) approx. | m | 0.50 | 0.50 | 0.50 | 0.50 | 0.50 | 0.50 | |
| | Depth (T) approx. | m | 0.20 | 0.20 | 0.25 | 0.25 | 0.20 | 0.20 | |
| | Length (L) approx. | m | 2.70 | 3.00 | 3.55 | 4.10 | 2.45 | 3.00 | 3.55 |
| Art.-No. | | 129673 | 129680 | 129703 | 129727 | 129741 | 129765 | 129789 | |



| Combi System | | | | | | | | |
|--------------|----------|----------|----------|----------|----------|----------|----------|----------|
| | 3x8-3x14 | 3x8-3x14 | 3x8-3x14 | 3x8-3x14 | 3x8-3x10 | 3x8-3x14 | 3x8-3x14 | 3x8-3x14 |
| Page 92 | ① | ② | ③ | ④ | ⑤ | ⑥ | ⑦ | ⑧ |