



STS 260A – Automatic mechanical filter cleaning without interrupting extraction

With standard pre-filter and HEPA filter. Suitable for construction, concrete, grinding and plaster dust. With 3-stage dust filtration: 1. Stage for coarse dust, 2. Stage with 99.9 % via a polyester pre-filter, 3. Stage via 2 x HEPA filters with 99.995 %. Dust is collected in a transparent and easily transportable plastic bag (Longbag).

Including hand tube with floor suction nozzle and rubber strip, brush strip, hose (length 5 /10 m, hose connection Ø 50 mm, antistatic), Longbag and cable ties.



Automatic mechanical filter cleaning



With click system for suction hose attachment

Technical data

Ref. No.		617004
Voltage	V	230
Frequency	Hz	50/60
Power input	kW	2,2
Operating weight	kg	71
Dimensions L x W x H	cm	92 x 45 x 145
Noise level	dB(A)	78
Suction hose, antistatic	m	5
Ø – suction outlet	mm	50
Underpressure	kPa	23
Suction capacity	m ³ /h	340
Filter cleaning		automatically
Filter class		HEPA 14

Special characteristics

- Robust in design
- Large abrasion-resistant transportation wheels
- Simple and reliable dust disposal via Longbag
- Simple hose connection with click system
- Automatic mechanical filter cleaning without suction interruption
- Antistatic hoses