



Information

FIS, Fibre Discs

Fibre-backed discs FIS are used on angle grinders with a backing pad STF. We offer this very popular product in NK, ZK and Ceramic for universal application.

SHF semi-flexible grinding disc

The SHF semi-flexible grinding disc consists of a stable fibre backing with a structured abrasive coating of silicon carbide. This combination is particularly suitable for coarse grinding work on the biggest variety of materials. Typical applications are the removal of paint, rust and adhesives, but also the processing of glass-fibre reinforced plastics such as GRP and CRP (e.g. during the manufacture of wind turbine blades). Like fibre discs, semi-flexible grinding discs for angle grinders are only used with an STF backing plate.

SPR, Economy rolls

We supply economy rolls manufactured from flexible coated abrasive for off-hand application. The appropriate length can be cut from the roll.

SVB, Fleece pads and SVR, Fleece rolls

We supply abrasive fleece economy rolls and pads used off-hand or on vibratory finishing machines. These can be used wet or dry.



Find (1/1)

A38301800363

Previous Next

High Performance

FIS, Fibre Disc with slotted hole, Ceramic grain Ordering example: A38301150243






Packing unit:
25 pcs. per type
 v_{max} : 80 m/s
ISO 16057
Ceramic = ceramic grain

Description	Grits	d ₁ mm	Bore mm	n _{max} (1/min)	Product-Number	recommended for
FIS 115	Ceramic 24	115	22	13.000	A38301150243	■
FIS 115	Ceramic 36	115	22	13.000	A38301150363	■
FIS 115	Ceramic 60	115	22	13.000	A38301150603	■
FIS 115	Ceramic 80	115	22	13.000	A38301150803	■
FIS 125	Ceramic 24	125	22	12.000	A38301250243	■
FIS 125	Ceramic 36	125	22	12.000	A38301250363	■
FIS 125	Ceramic 60	125	22	12.000	A38301250603	■
FIS 125	Ceramic 80	125	22	12.000	A38301250803	■
FIS 180	Ceramic 24	180	22	8.500	A38301800243	■
FIS 180	Ceramic 36	180	22	8.500	A38301800363	■

Industry

FIS, Fibre Disc with slotted hole, Zirconia Alum. Oxide Ordering example: A38301150242

Packing unit:
25 pcs. per type
 v_{max} : 80 m/s
ISO 16057
ZK = Zirconia Alum. Oxide

Description	Grits	d ₁ mm	Bore mm	n _{max} (1/min)	Product-Number	recommended for
FIS 115	ZK 24	115	22	13.000	A38301150242	■
FIS 115	ZK 36	115	22	13.000	A38301150362	■
			22	13.000	A38301150402	■
			22	13.000	A38301150602	■
			22	13.000	A38301150802	■

🖱️
👤
⏪
⏩
87.4%
📄
🔍
🔄
🏠
📤