



LIMEX
CROATIA
WHEELBARROWS
MIXERS

Poluteška vibro ploča PCLX 320 & 400

Midweight Plate Compactor PCL 320 & 400

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Veličina ploče Plate Size	Statički pritisak Static pressure
PCLX320 petrol Honda GX100	3.0ks/hp / 2.2 kW	320mm x 574mm	398 kg/m ²
PCLX400 petrol Honda GX100	3.0ks/hp 2.2 kW	400mm x 574mm	336 kg/m ²
Centrifugalna sila Centrifugal Force	Brzina puta Travel speed	Razina vibracije Vibration level	Masa Weight
13kN	20m/min.	2.42m/sec	62kg
13kN	20m/min.	2.48m/sec	66.5kg



Teška kombinirana vibro ploča PCX 12/36 & 13/40

Heavyweight Combination Plate Compactor PCX 12/36 & 13/40

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power (ks/hp / kW)	Veličina ploče (ŠxD) Plate Size (WxL)	Statički tlak Static Pressure	Centrifugalna sila Centrifugal Force	Brzina kretanja Travel Speed	Vibracija/Uporaba Vibration/usage	Masa Weight
Kompaktorne pločice sa vodenim kitom / Compactor Plates with water kit							
PCX 12/36	Honda Petrol GX120 4/3	360mm x 606mm	611kg/m ²	12.25kN	20m/min	4.74m/sec ² / 2.14h	84.5kg
PCX 13/40		400mm x 606mm	542kg/m ²	13kN		3.2m/sec ² / 4.53h	87kg
Kompaktorne pločice bez vodenog kita / Compactor Plates without water kit							
PCX 12/36	Honda Petrol GX120 4/3	360mm x 606mm	586kg/m ²	12.25kN	20m/min	4.74m/sec ² / 2.14h	81kg
PCX 13/40		400mm x 606mm	520kg/m ²	13kN		3.2m/sec ² / 4.53h	3.5kg





BELLE
LIGHT
CONSTRUCTION
EQUIPMENT



Specijalna "Delta" vibro ploča PCX 20/45 & 20/50

Special Delta Plate Compactor PCX 20/45 & 20/50

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Statički tlak Static Pressure	Centrifugalna sila Centrifugal Force	Brzina kretanja Travel Speed	Vibracija Vibration	Dimenzija (ŠxDxV) Dimensions (WxLxH)	Masa Weight
PCX 20/45 Honda GX160 Benzin/Petrol	5.5ks/hp / 4.0kW	463kg/m ²	20	26m/min	3.5m/sec ²	450x1167x987	91kg
PCX 20/45 Hatz 1B20 Dizel/Diesel	4.6ks/hp / 3.5kW	585kg/m ²	20	25m/min	2.64m/sec ²	450x1167x987	115kg
PCX 20/50 Honda GX160 Benzin/Petrol	5.5ks/hp / 4.0kW	442kg/m ²	20	25m/min	3.5m/sec ²	500x1167x987	97kg
PCX 20/50 Hatz 1B20 Dizel/Diesel	4.6ks/hp / 3.5kW	547kg/m ²	20	24m/min	2.45m/sec ²	500x1167x987	120kg



Teška vibro ploča PCX 450 & 500

Heavyweight Plate Compactor PCX 450 & 500

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Veličina ploče Plate Size	Statički pritisak Static Pressure	Centrifugalna sila Centrifugal Force	Brzina kretanja Travel Speed	Vibracija Vibration	Masa Weight
PCX benzin sa vodenim kitom/ PCX Petrol with Water Kit							
PCX 450 Honda	4ks/hp / 3kW	418mm x 470mm	382kg/m ²	16.5	23m/min	1.90m/sec ²	96kg
PCX 450 Hatz	4.6ks/hp / 3.5 kW	450mm x 696mm	440kg/m ²		22m/min	2.61m/sec ²	113kg
PCX 500 Honda	5.5ks/hp / 4.4kW	467mm x 470mm	351kg/m ²		19m/min	2.00m/sec ²	97.50kg
PCX 500 Hatz	4.6ks/hp / 3.5 kW	500mm x 696mm	404kg/m ²		19m/min	2.59m/sec ²	116kg
PCX Standardni/Asfaltni benzin bez vodenog kita / PCX Standard/Asphalt Petrol without Water Kit							
PCX 450 Honda	4ks/hp / 3kW	418mm x 470mm	382kg/m ²	16.5	23m/min	1.90 m/sec ²	86kg
PCX 450 Hatz	4.6ks/ hp / 3.5kW	450mm x 696mm	440kg/m ²		33m/min	2.45 m/sec ²	110.5kg
PCX 500 Honda	5.5ks/ hp / 4.4kW	467mm x 470mm	351kg/m ²		19m/min	2.00 m/sec ²	88kg
PCX 500 Hatz	4.6ks/hp / 3.5 kW	500mm x 696mm	404kg/m ²		19m/min	2.59 m/sec ²	114kg



Kompaktna reverzibilna vibro ploča RPC 30

Compact reversible plate compactor RPC 30

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine power	Veličina ploče (ŠxD) Plate Size (WxL)	Centrifugalna sila Centrifugal Force	Frekvencija Frequency	Težinski razred Weight Class	Masa Weight
RPC 30/40	Honda GX160 Benzin/Petrol 5.5ks/hp / 4kW	400mm x 657mm	30kN	90Hz	160	158kg
RPC 30/40D	Hatz 1B20 Dizel/Diesel 4.2ks/hp / 3.1kW					170kg
RPC 30/50	Honda GX160 Benzin/Petrol 5.5ks/hp / 4kW	500mm x 657mm			200	161kg
RPC 30/50D	Hatz 1B20 Dizel/Diesel 4.2ks/hp / 3.1kW					174kg



Reverzibilna vibro ploča srednje veličine RPC 45

Medium size reversible plate compactor RPC 45

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Veličina ploče (ŠxD) Plate size (WxL)	Centrifugalna sila Centrifugal Force	Frekvencija Frequency	Težinski razred Weight Class	Masa Weight
RPC 45/60	Honda GX270 Benzin/Petrol 9ks/hp / 6.7kW	600mm x 839mm	45kN	70Hz	300	275kg
RPC 45/60D	Hatz 1B30 Dizel/Diesel-6.3hp/4.7kW	600mm x 839mm	45kN	70Hz	300	291kg
RPC 45/60DE Električno paljenje / Electric start						
Narančasta / Orange	Hartz 1B30 Dizel/Diesel 6.3ks/hp / 4.7kW	600mm x 839mm	45kN	70Hz	300	303kg
Žuta / Yellow						



Reverzibilna vibro ploča za najteže radove RPC 60

Heavy duty reversible plate compactor RPC 60

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Veličina ploče (ŠxD) Plate size (WxL)	Centrifugalna sila Centrifugal Force	Frekvencija Frequency	Težinski razred Weight Class	Masa Weight
RPC 60/80D	Hatz 1D81Z Dizel/Diesel 15ks/hp / 11kW	700mm x 945 mm	60kN	70Hz	500	475kg
RPC 60/80D Električno paljenje / Electric start						
Narančasta / Orange	Hatz 1D81Z Dizel/Diesel 15ks/hp / 11kW	700mm x 945mm	60kN	70Hz	500	505kg
Žuta / Yellow						



RTX Stupni nabijač

RTX Rammer

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Udaraca u minuti Blows per Minute	Tip karburatora Carburettor Type	Sila udarca Impact Force	Širina x visina x dužina Width x Height x Length	Veličina stope (ŠxD) Foot Size (WxL)	Masa Weight
RTX 50 Honda Benzin/Petrol 230mm stopa/Foot	3ks/hp / 2.3kW	450-660	Dijafragma Diaphragm	12,5kN	345mm x 975mm x 670mm	230mm x 335mm	57,7kg
RTX 60 Honda Benzin/Petrol 165mm stopa/Foot	3ks/hp / 2.3kW	450-660	Dijafragma Diaphragm	13,6kN	345mm x 975mm x 670mm	165mm x 335mm	60kg
RTX 60 Honda Benzin/Petrol 230mm stopa/Foot	3ks/hp / 2.3kW	450-660	Dijafragma Diaphragm	13,6kN	345mm x 975mm x 670mm	230mm x 335mm	60kg
RTX 60 Honda Benzin/Petrol 280mm stopa/Foot	3ks/hp / 2.3kW	450-660	Dijafragma Diaphragm	13,6kN	345mm x 975mm x 670mm	280mm x 335mm	60kg
RTX 66 Honda Benzin/Petrol 280mm stopa/Foot	3.2ks/hp / 2.6kW	450-600	Plovak Float Chamber	16,5kN	425mm x 1065mm x 700mm	280mm x 335mm	79kg
RTX 68 Honda Benzin/Petrol 280mm stopa/Foot	3ks/hp / 2.3kW	450-660	Dijafragma Diaphragm	16kN	345mm x 1040mm x 705mm	280mm x 335mm	70kg
RTX 70 Honda Benzin/Petrol 280mm stopa/Foot	3ks/hp / 2.3kW	450-700	Dijafragma Diaphragm	17kN	345mm x 1040mm x 714mm	280mm x 335mm	72kg
RTX 74 Honda Benzin/Petrol 280mm stopa/Foot	3.2ks/hp / 2.6kW	450-600	Plovak Float Chamber	18,6kN	425mm x 1065mm x 700mm	280mm x 335mm	84kg
RTX 80 Yanmar Dizel/Diesel 280mm stopa/Foot	4.7ks/hp / 3.5kW	450-600	Ubrizgavanje Injection	20,5kN	425mm x 1081mm x 700mm	280mm x 335mm	86kg





BELLE
LIGHT
CONSTRUCTION
EQUIPMENT



Valjak TDX 650

Hand roller TDX 650

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Jačina motora Engine Power	Frekvencija Frequency	Brzina kretanja unaprijed Forward Travel Speed	Brzina kretanja unatrag Reverse Travel Speed	Sila Force	Širina bubnja Drum Width	Širina x visina x dužina Width x Height x Length	Masa Weight
TDX 650 Valjak TDX 650 Twin Drum roller	Yanmar L100N 10ks/hp / 7.4 kW	3300 vpm	> 3.9km/hr	> 2.1km/hr	20kN	650mm	702mm x 1093mm x 2272mm	775kg



Valjak TDX 650A

Twin Drum roller TDX 650A

TEHNIČKI PODACI / TECHNICAL SPECIFICATION



Model	Snaga motora Engine Power	Frekvencija Frequency	Brzina kretanja unaprijed Forward Travel Speed	Brzina kretanja unatrag Reverse Travel Speed	Sila Force	Širina bubnja Drum Width	Širina x visina x dužina Width x Height x Length	Masa Weight
TDX 650A Valjak TDX 650A Twin Drum roller	Yanmar L100N 10ks/hp / 7.4kW Električni Electric	3300 vpm	> 3.9km/hr	> 2.1 km/hr	16kN	650mm	703mm x 1137mm x 2318mm	675kg
TDX 650A Valjak TDX 650A Twin Drum roller	Kubota EA330 6.9ks/hp / 5.2 kW Električni Electric	3300 vpm	> 3.9km/hr	> 2.1 km/hr	16kN	650mm	703mm x 1137mm x 2318mm	684kg

Megavib Plus ručni vibrator

Megavib Plus Poker

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Brzina motora bez opterećenja Motor Speed Unloaded	Brzina motora pod opterećenjem Motor speed loaded	Snaga Power	Punjenje Loading	Masa Weight
Megavib+pogonska jedinica 110v Megavib+Drive Unit 110v	16 000 o/min / rpm	12 000 o/min / rpm	1.6kW	13A	4.8kg
Megavib+pogonska jedinica 230v (16 Amp-3 pin utikač/plug) Megavib+Drive Unit 230v (16 Amp-3 pin utikač/plug)			2.3kW	10A	

Model	Promjer vibro igle Poker Diameter	Duljina glave Head length	Duljina vratila Shaft Length	Frekvencija Frequency	Centrifugalna sila Centrifugal Force	Masa Weight
Megavib+Fleksibilno vratilo 3m Megavib+Flexible Shaft 3m						
Megavib+Vibroigla 36mm Megavib+Poker head 36mm	36mm - 1 1/4 inch	292mm	3m	217Hz	4018 N	1.9kg
Megavib+Vibroigla 50 mm Megavib+Poker head 50 mm	50mm - 2 inch	327mm		200Hz	5039 N	3.7kg
Megavib+Vibroigla 57mm Megavib+Poker head 57mm	57mm - 2 1/4 inch	346mm		192Hz	6468 N	5kg
Megavib+Vibroigla 25mm + 3m fleksibilno vratilo Megavib+Poker head 25mm + 3m Shaft	25mm - 1 inch	300mm		225Hz	882 N	5.5kg



BGN Plus / BGN Turbo električni visoko frekventni vibrator

BGN Plus / BGN Turbo Electric High Frequency Poker

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Promjer vibro igle Poker Diameter	Duljina vibro igle Head length	Promjer djelovanja Action Diameter	Amplituda vibracije Vibration Amplitude	Centrifugalna sila Centrifugal Force	Struja napajanja Supply Current	Masa Weight
BGN+ 35	36mm - 1 1/8 inch	350mm	304mm	0.98mm	1390 N	5 A	9kg
BGN+ 45	42mm-1 1/2 inch	320mm	349mm	1.00mm	2100 N	5 A	10kg
BGN+ 50	50mm - 2 inch	400mm	416mm	1.01mm	3485 N	7 A	14kg
BGN+ 60	58mm - 2 5/16 inch	430mm	480mm	1.12mm	5165 N	8.5 A	15kg
BGN+ 70	65mm - 2 9/16 inch	430mm	520mm	1.11mm	6670 N	13.2 A	18kg
BGN Turbo 52	52mm - 2 inch	382mm	520mm	1.02mm	3815 N	10 A	14kg
BGN Turbo 58	58mm - 2 5/16 inch	410mm	580mm	1.09mm	5520 N	11 A	16kg
BGN Turbo 65	65mm - 2 9/16 inch	425mm	650mm	1.13mm	7275 N	13 A	18kg
BGN Turbo 75	75mm - 3 inch	430mm	750mm	1.22mm	8460 N	14 A	21kg



Visoko frekventni pretvarač BGF

High Frequency Converters BGF



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Na- pon Supply Input	Faza Phase	Broj izlaznih utičnica No. of Output Sockets	Izlazna struja Output Current	Širina x visina x duljina Width x Height x Length	Masa Weight
BGF 20 Visoko frekventni pretvarač / BGF 20 High Frequency Converter	230 V	3	2	20 A	170mm x 460mm x 320mm	18 kg
BGF 24 Visoko frekventni pretvarač / BGF 24 High Frequency Converter	230 V	1	2	21 A	270mm x 385mm x 525mm	28 kg
BGF 24T Visoko frekventni pretvarač / BGF 24T High Frequency Converter	400 V	3	2	21 A	270mm x 385mm x 525mm	32 kg
BGF 34T Visoko frekventni pretvarač / BGF 34T High Frequency Converter	400 V	3	3	34 A	445mm x 510mm x 560mm	34 kg
BGF 64T Visoko frekventni pretvarač / BGF 64T High Frequency Converter	400 V	3	4	64 A	451mm x 570mm x 930mm	85 kg

MidiScreed 200 Kompaktna vibro letva

MidiScreed 200 Compact Screeder

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Brzina Speed	Vibracija Vibration	Širina letve Beam Width	Duljina ručke Handle Length	Visina pogonske jedinice Power Unit Height	Širina pogonske jedinice Power Unit Width	Masa Weight
MidiScreed 200 Honda Benzin/Petrol	1ks/hp / 0.71kW	7000 o/min / rpm	2.3kN	2000mm	2000mm	408mm	398mm	19kg



Easy Screed Pro Vibro letva

Easy Screed Pro Screeder

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Frekvencija Frequency	Max. dubina zbijanja Max. Compaction Depth	Širina x visina x dužina Width x Height x Length	Masa Weight
Benzinska pogonska jedinica - Easy Screed Pro Petrol Drive Unit- Easy Screed Pro	1.3ks/hp / 1kW	83Hz	75mm	700mm x 440mm x 1040mm	14.6kg
Easy Screed - Letva / Beam 1.9m	-	-	-	200mm x 100mm x 1900mm	7.8kg
Easy Screed - Letva / Beam 2.5m	-	-	-	200mm x 100mm x 2500mm	10.3kg
Easy Screed - Letva / Beam 3m	-	-	-	200mm x 100mm x 3000mm	12.3kg
Easy Screed - Letva / Beam 3.75m	-	-	-	200mm x 100mm x 3750mm	15.4kg
Easy Screed - Letva / Beam 4.25m	-	-	-	200mm x 100mm x 4250mm	17.5kg
Easy Screed - Letva / Beam 5m	-	-	-	200mm x 100mm x 5000mm	20.5kg
Easy Screed - Letva / Beam 5.5m	-	-	-	200mm x 100mm x 5500mm	22.6kg
Easy Screed - Letva / Beam 6m	-	-	-	200mm x 100mm x 6000mm	24.6kg





BELLE
LIGHT
CONSTRUCTION
EQUIPMENT



Ravnalica

Floats

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Širina Width	Dubina Depth	Ukupna dužina ručke Total Handle Length	Masa glave sa zglobovom Head Weight c/w Swivel	Ukupna masa ručke Total Handle Weight
Letva od legure magnezija sa zglobovom i drškom Bull Float c/w Swivel & Handle	1200mm	200mm	5.4m	6kg	3.6kg
Letva od kaljenog čelika sa zglobovom i drškom Big Blue c/w Swivel & Handle	1200mm	300mm	5.4m	11.1kg	3.6kg
Kombinirani alat za zagladenu površinu sa zglobovom i drškom Fresno Broom c/w Swivel & Handle	900mm	220mm	5.4m	4.8 kg	3.6kg



Alati Tools



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Širina Width	Dubina Depth	Ukupna dužina ručke Total Handle Length	Masa glave sa zglobovom Head Weight c/w Swivel	Ukupna masa ručke Total Handle Weight
Alat za navlačenje betona Concrete Placer	495mm	115mm	1.4m	1.5kg	0,5kg
Grablje za navlačenja betona Concrete Rake	570mm	130mm	1.4m	1.5kg	0,5kg

Pribor za betoniranje

Concreting Accessories

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Pribor Pro Gladilice / Pro Trowels Accessories
Noževi i diskovi su visokokvalitetne izrade kako bi dali najbolju izvedbu za Vašu Pro gladilicu High quality Blades and Discs to give the best performance from Your Pro Trowel
600mm Gladilice, noževi i diskovi / 600mm Trowel, Blades and Discs
PRO 600 Završne gladilice na vijak / Bolt on Finish Blades, 4
PRO 600 / PRO 600X Plutajući disk/ploča Float Disc / Pan
900mm Gladilice, noževi i diskovi / 900mm Trowel, Blades and Discs
PRO 900 Plutajuće gladilice / Float blades, 4
PRO 900 Završne gladilice / Finish blades, 4
PRO 900 Kombinirane gladilice / Combination blades, 4
PRO 900 Plutajući disk/ploča / Float Disc / Pan
1200mm Gladilice, noževi i diskovi / 1200mm Trowel, Blades and Discs
PRO 1200 Plutajuće gladilice / Float blades, 4
PRO 1200 Završne gladilice / Finish blades, 4
PRO 1200 Kombinirane gladilice / Combination blades, 4
PRO 1200 Plutajući disk/ploča / Float Disc / Pan
Gladilice sa kvačicom za Dynapac / Clip-on finish blades for Dynapac (BG33, BG37, BG38)
Kitovi kotača / Wheel Kits
Kit-kotač gladilice / Trowel Wheel Kit



Lightweight Pro / Pro Tilt gladilica

Lightweight Pro / Pro Tilt Trowel

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Pogonska snaga Drive Power	Promjer zagladivanja Trowelling Diameter	Brzina zagladivanja Trowelling Speed	Širina x visina x dužina Width x Height x Length	Masa Total Handle Weight
Lightweight Pro 900M GX160 Honda	5.5ks/hp / 4kW	925mm	65-131 o/min / rpm	992mm x 781mm x 1866mm	79,5kg
Lightweight Pro 900M GX160 Honda sa sklopivom ručkom/foldable Handle	5.5ks/hp / 4kW	925 mm	65-131 o/min / rpm	992mm x 932mm x 2013mm	81kg
Lightweight Pro 900M EX17 Robin	6ks/hp / 4.5kW	925mm	65-131 o/min / rpm	992mm x 781mm x 1866mm	79.5kg
Lightweight Pro 900M EX17 Robin sa sklopivom ručkom/Foldable Handle	6ks/hp / 4.5kW	925mm	65-131 o/min / rpm	992mm x 932mm x 2013mm	81kg
Lightweight Pro 900M GX270 Honda	9ks/hp / 6.7kW	925mm	65-131 o/min / rpm	992mm x 781mm x 1866mm	88kg
Lightweight Pro 900M GX 270 Honda sa sklopivom ručkom/Foldable Handle	9ks/hp / 6.7kW	925mm	65-131 o/min / rpm	992mm x 932mm x 2013mm	89.5kg
Lightweight Pro Tilt 900M GX160 Honda	5.5ks/hp / 4kW	925mm	65-155 o/min / rpm	995mm x 781mm x 1855mm	79,5kg
Lightweight Pro 900M EX17 Robin	5.5ks/hp / 4kW	925mm	65-155 o/min / rpm	995mm x 781mm x 1866mm	79,5kg



Pro 600X gladilica

Pro 600X Trowel

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Pogonska snaga Drive Power	Promjer zagladivanja Trowelling Diameter	Brzina zagladivanja Trowelling Speed	Širina x visina x dužina Width x Height x Length	Masa Total Handle Weight
Pro 600X GX120 Honda benzin/Petrol	4ks/hp / 3kW	600mm-24inch	50-115 o/min / rpm	600mm x 930mm x 1500mm	53kg
Pro 600X električni/Electric 230v	3ks/hp / 2.1kW	600mm-24inch	115 o/min / rpm	600mm x 930mm x 1500mm	73kg

Pro gladilica

Pro Trowel

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Pogonska snaga Drive Power	Promjer zagladivanja Trowelling Diameter	Brzina zagladivanja Trowelling Speed	Širina x visina x dužina Width x Height x Length	Masa Total Handle Weight
Lightweight Pro 900M GX200 Honda	5.5ks/hp / 4kW	925mm	65-131 o/min / rpm	992mm x 781mm x 1866mm	79,5 Kg
Lightweight Pro 900M GX200 Honda sa sklopivom ručkom / Foldable Handle	5.5ks/hp / 4kW	925mm	65-131 o/min / rpm	992mm x 932mm x 2013mm	81kg
Lightweight Pro 900M EX17 Robin	6ks/hp / 4.5kW	925mm	65-131 o/min / rpm	992mm x 781mm x 1866mm	79,5kg
Lightweight Pro 900M EX17 Robin sa sklopivom ručkom / Foldable Handle	6ks/hp / 4.5kW	925mm	65-131 o/min / rpm	992mm x 932mm x 2013mm	81kg
Lightweight Pro 900M GX270 Honda	9ks/hp / 6.7kW	925mm	65-131 o/min / rpm	992mm x 781mm x 1866mm	88kg
Lightweight Pro 900M GX270 Honda sa sklopivom ručkom / Foldable Handle	9ks/hp / 6.7kW	925mm	65-131 o/min / rpm	992mm x 932mm x 2013mm	89,5kg
Pro 1200M GX270 Honda	9ks/hp / 6.7kW	1170mm	65-131o/min / rpm	1206mm x 1008mm x 2130mm	117kg
Pro 1200M GX270 Honda sa sklopivom ručkom / Foldable Handle	9ks/hp / 6.7kW	1170mm	65-131o/min / rpm	1206mm x 1008mm x 2130mm	117kg
Pro 1200M EX27 Robin	9ks/hp / 6.7kW	1170mm	65-131rpm	1206mm x 1008mm x 2130mm	117kg
Pro 1200M EX27 Robin sa sklopivom ručkom / Foldable Handle	9ks/hp / 6.7kW	1170mm	65-131rpm	1206mm x 1008mm x 2130mm	117kg





BELLE
LIGHT
CONSTRUCTION
EQUIPMENT



Pro Tilt gladilica s brzim podešavanjem nagiba / Pro Tilt Trowel

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Pogonska snaga Drive Power	Promjer zaglađivanja Trowelling Diameter	Brzina zaglađivanja Trowelling Speed	Širina x visina x dužina Width x Height x Length	Težina ručke Total Handle Weight
Pro Tilt 900M GX200 Honda	5,5ks/hp / 4kW	925mm	65-155 o/min / rpm	992mm x 1005mm x 2021mm	98,5kg
Lagana/Lightweight Pro Tilt 900M GX200 Honda	5,5ks/hp / 4kW	925mm	65-155 o/min / rpm	995mm x 781mm x 1866mm	79,5kg
Pro Tilt 1200M GX270 Honda	9ks/hp / 6.7kW	1140mm	65-155 o/min / rpm	1206mm x 1008mm x 2130mm	117kg



BC350 električna stolna rezalica

BC350 Electric bench saw

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Minimalna snaga transformatora Minimum Transformer Size
BC350 Električna rezalica za cigle 110v 32 Amp / BC350 Brick Saw Electric 110v 32 Amp	3ks/hp / 2.2kW	5 kVA
BC350 Električna rezalica za cigle 230v 16 Amp / BC350 Brick Saw Electric 230v 16 Amp	3ks/hp / 2.2kW	N/A

Struja Current Supply	Veličine rezne ploče Blade size	Brzina rezne ploče Blade speed	Širina x visina x dužina Width x Height x Length	Masa Weight
32Amp	350mm x 25.4mm	3000o/min / rpm	684mm x 1379mm x 1212mm	79kg
16Amp	350mm x 25.4mm	3000o/min / rpm	684mm x 1379mm x 1212mm	79kg

Dijamantne rezne ploče Diamond Blades



Vrsta ploče / Disc Qualita	PLATINUM ★★★★★	GOLD ★★★★★	GOLD ★★★★★	GOLD ★★★★★	BRONZE ★★	MISC ★★★★
Materijal aplikacije / Application Material	Razni materijali Multi Materials	Teški materijali Hard Materials	Opći materijali General Materials	Asfalt Asphalt	Osnovna upotreba General Purpose	Ravni rub Continuous Rim Tile Cutting
Product code	PUX	GH	GGP	GA	BGP	CRT
Šipka od nehrđajućeg čelika i pojačanje / Mild Steel Rods & reinforcement	★★	✗	✗	✗	✗	✗
Cijev za skele / Scaffolding Tube	★★	✗		✗	✗	✗
Granit/ Granite	★★★	★★★	✗	✗	✗	★★★★
Keramika, kamen, podne pločice od škriljca / Ceramir, Quarry, Floor & Slate Tiles	✗	✗	✗	✗	✗	★★★★
Blokovi / Engineering Blocks	★★★	★★★	✗	✗	✗	✗
Stari beton / Old Cured Concrete	★★★	★★★	✗	✗	✗	✗
Glinene cijevi / Clay Pipes	★★★	★★★	✗	✗	✗	✗
Glinena opeka / Dense Clay Bricks	★★★	★★★	✗	✗	✗	✗
Glineni opločnici / Clay Hard Pavers	★★★	★★★	★	✗	✗	✗
Tvrda opeka / Hard Facing Bricks	★★★	★★★	★	✗	★	✗
Betonska ploča za popločavanje / Concrete Paving Slabs	★★★	★★★	★★	✗	★	✗
Armirani betonski nadvoji / Reinforced Concrete Lintels	★★★	★★	★★★	✗	★	✗
Popravljeni beton / Cured Concrete	★★★	★	★★★	✗	★★	✗
Betonske cijevi i ivičnjaci / Concrete Pipes & Kerbs	★★★	★	★★★	✗	★★	✗
Srednje tvrda opeka / Medium Facing Bricks	★★★	★	★★★	✗	★★	✗
Tvrđi pješćanjak / Hard sandstone	★★★	★	★★★	✗	★	✗
Škriljevac/ Slate	★★★	✗	★★★	✗	★	✗
Srednje tvrdi opločnici / Medium Blocks Pavers	★★★	✗	★★★	✗	★	✗
Betonski crijep / Concrete Roofing tile	★★★	✗	★★	✗	★	✗
Srednje tvrdi pješćanjak / Medium sandstone	★★★	✗	★	★	★★	✗
Asfalt preko betona / Asphalt Over Concrete	★★★	✗	✗	★★	✗	✗
Lagani blok / Breeze Blocks	★★★	✗	★	★★	★	✗
Zeleni beton / Green Concrete	★★★	✗	✗	★★★		✗
Lignacit i zračni blok / Lignacite & Aerated Blocks	★★★	✗	✗	★★★	✗	✗
Asfalt / Asphalt	★★★	✗	✗	★★★	✗	✗

★★★★ Visoka izvedba / High Performance

★★★ Dobra izvedba / Good Performance

★★ Preporučeno / Recommended

★ Prihvatljivo / Acceptable

✗ Ne odgovara / Not Suitable



LIMEX
CROATIA
WHEELBARROWS
MIXERS

PUX



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Veličina Size	Brzina Speed	Visina reznog dijela Segment Height
PUX/30020	300mm x 20mm	6360 o/min / rpm	10mm
PUX/35025	350mm x 25mm	5450 o/min / rpm	10mm
PUX/45025	450mm x 25mm	3395 o/min / rpm	12mm

GH



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Veličina Size	Brzina Speed	Visina reznog dijela Segment Height
GH/30020	300mm x 20mm	6360 o/min / rpm	15mm
GH/35025	350mm x 25mm	5450 o/min / rpm	15mm
GH/45025	450mm x 25mm	3395 o/min / rpm	15mm

GGP



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Veličina Size	Brzina Speed	Visina reznog dijela Segment Height
GGP/35025	350mm x 25mm	5450 o/min / rpm	15mm
GGP/45025	450mm x 25mm	3395 o/min / rpm	15mm
GGP/50025	500mm x 25mm	5450 o/min / rpm	15mm

GA



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Veličina Size	Brzina Speed	Visina reznog dijela Segment Height
GA/30020	300mm x 20mm	6360 o/min / rpm	10mm
GA/35025	350mm x 25mm	5450 o/min / rpm	10mm
GA/45025	450mm x 25mm	3395 o/min / rpm	10mm

BGP



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Veličina Size	Brzina Speed	Visina reznog dijela Segment Height
BGP/23022	230mm x 22mm	6650 o/min / rpm	10mm
BGP/30020	300mm x 20mm	6360 o/min / rpm	10mm

CRT



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Veličina Size	Brzina Speed	Visina reznog dijela Segment Height
CRT/18025	180mm x 25mm	8730 o/min / rpm	10mm
CRT/20025	200mm x 25mm	7600 o/min / rpm	10mm
CRT/23025	230mm x 25mm	6650 o/min / rpm	10mm

Rezač betonskih blokova Minipave

Block Paving splitter Minipave

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Sila rezanja Cut Force	Vrsta oštrice Blade Type	Pomak škara Cam Movement	Vijci za pomicanje Adjustment Screws	Dubina bloka Block Depth	Maks. duljina reza Max. cut Length	Masa Weight
Minipave	3200kg - 31,4kN	2 od 8mm kvadratnog presjeka 2 off 8mm square section 250mm duljina/long	po bloku/block clearance 3mm za rezanje/cutting 2mm	Brzo djelujući trapezoidni 40mm Fast Acting Trapezoid 40mm	47-87 mm	250mm	18kg





BELLE
LIGHT
CONSTRUCTION
EQUIPMENT



Rezač betonskih Maxipave blokova

Block Paving Maxipave splitter

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Sila rezanja Cut Force	Dužina oštrice Blade Length	Maks. dužina reza Max. cut Length	Masa Weight
Maxipave	45,6kN	408mm	120mm	35,5kg



Rezač pločica Maxitile 260

The saw Maxitile 260

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Motor Power	Veličina noža Blade Size	Veličina oštrice noža Blade ID Bore Size	Max. dubina rezanja Max. Depth of Cut
Maxitile 260 230v	650w	200mm	25,4mm	40mm
Max. dužina reza Max. Length of cut	Kapacitet spremnika Tank Capacity	Širina x Visina x Dužina Width x Height x Weight		Masa Weight
650mm	20.5L	440mm x 1160mm x 1250mm		34kg



Alati za popločavanje

Block Paving Tools

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model
Klin za razmak / Gap Wedge
Podizač za blokete / Block Lifter
Malj za blokete / Block Mallet
Podizač odrezanih bloketa / Block Clip Lifter 200
Podizač odrezanih bloketa / Block Clip Lifter 800



Hidraulični čekići

BHB Hydraulic Breakers

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Razina vibracije Vibration Level-Midi Power Pack	Razina vibracije Vibration Level-Major Power Pack	Prigušnica Restrictor
BHB 12	16.08 m/sec2	-	Otvorena/Open
BHB 19	11.97 m/sec2	-	Otvorena/Open
BHB 23	11.97 m/sec2	-	Otvorena/Open
BHB 25	11.1 m/sec2	11.1 m/sec2	3.8
BHB 25x	6.5 m/sec2	6 m/sec2	Otvorena/Open
BHB 27	11.8 m/sec2	11.8 m/sec2	3.4
BHB 27	-	18.61 m/sec2	Otvorena/Open
BHB 27X	8.2 m/sec2	-	3.4
BHB 27X	-	6.8 m/sec2	Otvorena/open

Radni pritisak Working Pressure	Max. pritisak Max. Pressure	Protok Flow	Udaraca/min Blows/min	Sila razbijanja Breaking Force	Veličina čeličnog dijela Steel Size	Masa Weight
70-90 bar	160 bar	20 L/min	2400	25 džula/Joules	22mm x 82mm	14kg
90-110 bar	160 bar	20 L/min	1600	65 džula/Joules	25mm x 108mm	19kg
90-110 bar	160 bar	20 L/min	1600	65 džula/Joules	25mm x 108mm	23.5kg
105-125 bar	160 bar	20 L/min	1300	85 džula/Joules	32mm x 160mm	28kg
90-110 bar	160 bar	20 L/min	1600	55 džula/Joules	32mm x 160mm	27.5kg
105-125 bar	160 bar	20 L/min	1300	85 džula/Joules	32mm x 160mm	28kg
105-125 bar	160 bar	30 L/min	2150	85 džula/Joules	32mm x 160mm	28kg
105-125 bar	160 bar	20 L/min	1300	85 džula/Joules	32mm x 160mm	30kg
105-125 bar	160 bar	30 L/min	2150	85 džula/Joules	32mm x 160mm	30kg



Pribor za čekić

Breaker Steel



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Tip / Type	Dimenzije / Dimensions			
		Ulazni vrh / Collar to tip		Oštrica širina x visina / Blade width x height	
		(mm)	(inch)	(mm)	(inch)
Čelični nastavci / Steels 32 x 160mm (1¼ x 6¼") odgovara / to fit BHB25, BHB25 X, BHB27, BHB19USA					
Špica / Moil Point 32mm	1	380	15	-	-
Velika špica / Large Moil Point 32mm	1	455	18	-	-
Dlijeto 32mm / Chisel 32mm	2	380	15	-	-
Veće dlijeto 32mm / Large Chisel 32mm	2	455	18	-	-
Široko dlijeto 32m / Broad Chisle 32mm	4	380	15	75x50	3x2
Veliko i široko dlijeto 32m / Large Broad Chisle 32mm	4	455	18	75x50	3x2
Razbijač asfalta 32mm / Asphalt Cutter 32mm	5	380	15	125x50	5x2
Veliki razbijač asfalta 32mm / Large Asphalt Cutter 32mm	5	330	13	125x150	5x6
Sjekač za asfaltne zakrpe / Tarmac Cutter 32mm	6	280	11	115x125	4½x5
Sjekač za kopanje / Digging Chisel 32mm	7	355	14	75x230	3x9
Lopatica za kopanje / Digging Spade 32mm	8	355	14	125x20	5x8
Lopatica za glinu / Clay Spade 32mm	9	380	15	140x230	5½x9
Probijač / Stem 32mm	10	230	9	-	-
Stopa nabijača / Rammer Pad (32mm)	11	180 dia	7 dia	-	-
Čelični nastavci / Steels 25 x 108mm (1 x 4¼) odgovara / to fit BHB19, BHB23					
Špica / Moil Point 25mm	1	380	15	-	-
Velika špica / Large Moil Point 25mm	1	455	18	-	-
Dlijeto / Chisel 25mm	2	380	15	-	-
Veće dlijeto / Large Chisel 25mm	2	455	18	-	-
Široko dlijeto / Broad Chisel 25mm	4	380	15	75x50	3x2
Veliko i široko dlijeto / Large Broad Chisel 25mm	4	455	18	75x50	3x2
Veliki razbijač asfalta / Large Asphalt Cutter 25mm	5	380	15	125x150	5x6
Sjekač za asfaltne zakrpe / Tamac Cutter 25mm	6	305	12	115x125	4½x5
Sjekač za kopanje / Digging Chisel 25mm	7	355	14	75x230	3x9
Lopatica za kopanje / Digging Spade 25mm	8	355	14	125x200	5x8
Lopatica za glinu / Clay Spade 25mm	9	355	16	125x200	5x8
Probijač / Stem 25mm	10	200	8	-	-
Stopa nabijača / Rammer Pad (25&25mm)	11	125 dia	5 dia	-	-
Rastavljač željezničkih spojnica / Rail Clip Extractor		370	14¼	55x100	2¼x4
Čelični nastavci / Steels 22 x 82mm (7/8 x 3¼) odgovara / to fit BHB12					
Špica / Moil Point 22mm	1	380	15	-	-
Velika špica / Large Moil Point 22mm	1	455	18	-	-
Dlijeto / Chisel 22mm	2	380	15	-	-
Veće dlijeto / Large Chisel 22mm	2	455	18	-	-
Široko dlijeto / Broad Chisel 22mm	4	380	15	75X50	3X2
Veliko i široko dlijeto / Large Broad Chisel 22mm	4	455	18	75X50	3X2
Veliki razbijač asfalta / Large Asphalt Cutter 22mm	5	380	15	125X150	5X6
Sjekač za kopanje / Digging Chisel 22mm	7	355	14	75X230	3X9
Lopatica za glinu / Clay Spade 22mm	9	405	16	125X200	5X8
Probijač / Sterm 22mm	10	200	8	-	-
Stopa nabijača / Rammer Pad (25 & 22mm)	11	125 dia	5 dia	-	-



BELLE
LIGHT
CONSTRUCTION
EQUIPMENT



Agregat Bulldog

Power Packs Bulldog

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power	Duljina crijeva Hose length	Tlak Pressure	Protok Flow
Bulldog Honda Benzinski motor Bulldog Honda Petrol	9.0ks/hp / 6.6kW	6.75m	140bar	20L/min.
Bulldog Honda Benzinski motor + ladica za alat Bulldog Honda Petrol + Tool Tray	9.0ks/hp / 6.6kW	6.75m	140bar	20L/min.

Kapacitet spremnika za ulje Oil Tank Capacity	Kapacitet spremnika za gorivo Fuel Tank Capacity	Širina x visina x dužina Width x Height x Length	Masa Weight
5.6L	6.0L	515mm x 620 mm x 705mm	59,5kg
5.6L	6.0L	683mm x 320mm x 705mm	59,5kg



HPP Hidraulični agregati

HPP Hydraulic Power Packs

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Motor Engine Power	Tlak Pressure	Protok Flow	Širina x visina x dužina Width x Height x Length	Masa Weight
MIDI 20-140 HONDA GX 270 UK	9.0ks/hp / 6.6kW	140bar	20L/min.	555mm x 620mm x 740mm	60kg
MAJOR 30-140 HONDA GX 390	13.0ks/hp / 9.6kW	140bar	30L/min.	555mm x 620mm x 740mm	72kg
MIDI 20-140 HONDA GX 270	9.0ks/hp / 6.6kW	140bar	20L/min.	555mm x 620mm x 740mm	60kg
MIDI 20-110D Diesel Lombardini	7.5ks/hp / 5.5kW	110bar	20L/min.	555mm x 620mm x 740mm	67kg
MAJOR 20-160X HONDA GX 390	13.0ks/hp / 9.6kW	160bar	20L/min.	555mm x 620mm x 740mm	72kg



HDC 350 hidraulični rezač

HDC 350 Disc Cutter

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Protok ulja Oil flow	Maksimalni tlak Max pressure	Broj okretaja Revolutions	Brzina Speed		
HDC 350 Hidraulični rezač HDC 350 Hydraulic Disc Cutter	20-30L/min,	170bar	2500-4000 o/min / rpm	46-75m/s		
Veličina noža Blade size	Veličina otvora Arbor size	Dubina rezanja Cutting depth	3-osi razine vibracije 3-axis Vibration Level	Razina zvuka Sound Power Level	Masa sa crijevom Weight inc. Hoses	Masa sa rezačem Service Weight inc. Blade
350mm	25.4mm	133mm	4.9m/sec2	108dB(A)	12kg	13.5kg



Hidraulična vodena pumpa

Hydraulic Water Pump

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Kapacitet Capacity	Crijevo za pražnjenje Discharge Hose	Hidraulički protok Hydraulic Flow	Tlak ulja Oil Pressure	Masa pumpe Weight of Pump alone	Masa pumpe sa crijevom Weight Of Pump With hose
Pumpa za vodu Heavy duty water pump	52m³/h	50mm/2'	20L/min.	140bar	10kg	26kg
2" Crijevno za pražnjenje 2" Discharge Hose						
Glavni set crijeva Main hose set						



BMD 300 Minidumper

BMD 300 Minidumper

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Motor Power	Kapacitet spremnika za gorivo Fuel Tank Capacity	Maksimalna brzina kretnje naprijed Max. Travel Speed Fwd
BMD 300 Višenamjenske gume BMD 300 Multi-purpose tyres	Honda Benzin/Petrol GXV160 5.5ks/hp / 4 kW	2.5L	6km/h
BMD 300 Plutajuće gume BMD 300 Flotation Turf Tires			

Maksimalna brzina kretanja unatrag Max. Travel Speed Rev	Utovarni kapacitet Skip Capacity - Level Filled	Utovarni kapacite krupnog materijala Skip Capacity - Heaped	Širina x visina x dužina Width x Height x Length	Masa Weight
2.6km/h	113L	134L	716mm x 934mm x 1609mm	155kg
			1004mm x 934mm x 1609mm	195kg



BMD 300 Nosiva ploča bez stranica

BMD 300 Flatbed

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Ukupna duljina Overall Legth	Ukupna širina Overall Width	Ukupna visina Overall Height
BMD 300 Nosiva ploča bez stranica BMD 300 Flatbed	1550mm	716mm	1030mm
Masa stroja Machine Weight	Masa nosive ploče Flatbed Weight	Površina Surface Area	Korisna nosivost Max. Payload
143,2kg	13,2kg	0,35m ²	300kg

BMD 300 Rampa

BMD 300 Ramps

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Ukupna duljina Overall Legth	Duljina gornjeg dijela Length - Top Section	Duljina srednjeg dijela Lenght - Middle Section	Duljina donjeg dijela Lenght - Bottom Section
BMD 300 Rampa BMD 300 Ramps	3966mm	1144mm	1500mm	1305mm
Maksimalna visina Max. Height	Maksimalna širina gornjeg dijela Max. Width Top Section	Maksimalna širina donjeg dijela Max. Width Bottom Section	Masa po sekciji Weight Per Section	
1250mm	786mm	953mm	30kg	



BMD 300 Ralica za snijeg

BMD 300 Snow Plough

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Ukupna duljina Overall Legth	Ukupna širina Overall Width
BMD 300 Ralica za snijeg BMD 300 Snow Plough	1810mm	940mm
Ukupna visina Overall Height	Masa stroja Machine Weight	Masa ralice za snijeg Snow Plough Weight
1150mm	195kg	140kg



BELLE
LIGHT
CONSTRUCTION
EQUIPMENT



BMD 300 sa gumama za travu

BMD 300 Turf Tyres

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Ukupna dužina Overall Length	Ukupna širina Overall Width	Ukupna visina Overall Height
BMD 300 sa gumama za travu BMD 300 Turf Tyres Option	1550mm	1004mm	1588mm

Masa stroja Machine Weight	Masa gume Turf Tyres Weight	Tlak guma Turf Tyres Pressure	Veličina gume Turf Tyre Size
195kg	10kg	1.5bar	50cm x 25cm - 20cm 20in x 10in - 8in



GPX Agregati

GPX Generators



TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Snaga motora Engine Power 3000rpm	PRP Snaga/ Rating	COP Snaga/Rating (Kontinuirano/Continuous)
GPX 2700 Honda GX200 Benzin / Petrol	4.3ks/hp / 3.3kW	2.2kW	2.0kW
GPX 3400 Honda GX200 Benzin / Petrol	4.3ks/hp / 3.3kW	2.7kW	2.5kW
GPX 5000 Honda GX270 Benzin / Petrol	6.2ks/hp / 4.6kW	4.0kW	3.6kW
GPX 5000 Honda GX270 Benzin / Petrol + kotači/ Wheel Kit	6.2ks/hp / 4.6kW	4.0kW	3.6kW

Broj utičnica No. of Sockets			Spremnik za gorivo Fuel Tank	Frekvencija Frequency	Dimenzije Dimensions	Masa Weight
110V 16a	230V 16a	110V 32a			Š x V x D W x H x L	
1	1	-	3.1L	50Hz	432mm x 515mm x 618mm	46kg
1	1	1	3.1L	50Hz	432mm x 515mm x 618mm	47kg
2	1	1	5.6L	50Hz	512mm x 595mm x 728mm	64kg
2	1	1	5.6L	50Hz	778mm x 552mm x 661mm	79kg

GPX Jedinica za testiranje

GPX Test Unit

TEHNIČKI PODACI / TECHNICAL SPECIFICATION

Model	Nazivni napon Nominal Voltage	Raspon napona Voltage Range	Faza Phase	Frekvencija Frequency
GPX Jedinica za testiranje GPX Test Unit	110V/230V	0-300V	1	45-65Hz

Broj izlaznih utičnica Output Sockets		Duljina kabela Cable Length	Dimenzije Dimensions Š x V x D W x H x L	Masa Weight
110V 16a	230V 16a			
1	1	2 m	220mm x 253mm x 281mm	4.2kg

