

## CUP BRUSHES



Appearance can vary from picture depending on variant.





## CUP BRUSHES, KNOTTED WIRE 180-230 EVOLUTION \* \* \* \* \*

Knotted cup brush, high-end quality, for use on angle grinders

- High-performance wire developed by Osborn
- Particularly cost-effective
- Long life, high tensile strength, high breaking strain and short set-up times
- Special feature: individual knot ends are slightly open, so that the wire tips are in use immediately and directly
- Higher removal rate, aggressive cleaning performance

**Applications:** Paint/rust removal, deburring, descaling, removal of slag, silicate residues and blue discolouration, cleaning of fill layers and surfaces in the oil and gas industries

						Osborn steel / 0.50		Osborn steel / 0.80			
	0	Ť	G	Max. RPM	8	Order no.	€ per pcs	Order no.	€ per pcs	Order no.	C per pcs
	90	32	M14x2.0	7500	6	9906-033 125					
	90	32	58*	7500	6	9906-033 126					
	150	45	5/8"	6000	1			9906-033 021			
	150	45	5/8"	6000	1	9906-033 030					
	150	45	M14x2.0	6000	1	9906-033 031 1					



Appearance can vary from picture depending on variant





## CUP BRUSHES, KNOTTED WIRE

0-230 PERFECT ★★☆☆

Knotted cup brush, craftsman quality, for use on angle grinders

- Osborn bestseller in the DIY sector
- Good cleaning performance
- Best price/performance ratio
- Easy cleaning of larger areas

Applications: Paint/rust removal, removal of slag



Available in practical PET packaging with Euro-standard hole.



	T	G	Max. RPM	B	■ Steel / 0.35 ■		Steel / 0.50			
0					Order no.	€ per pcs	Order no.	€ per pcs	Order no.	€ per pcs
65	20	M14x2.0	12500	10	2008-608 131		2008-608 151			
75	27	M14x2.0	11000	10			2008-608 152			
80	22	M14x2.0	8500	10			2008-608 153			
100	22	M14x2.0	8500	5			2008-608 154			