

	Тегло на чука*	Тегло на багера	Работно налягане	Дебит	Ударна честота	Ниво на шума	Диаметър на работния инструмент	Макс. хидравлична мощност	Височина на чука	
									без инструмент	с инструмент
	kg	t	bar	l/min	bpm	dB(A)	mm	kW	mm	mm
EC40T	95	1-3	110-130	15-35	560-1600	109	42	8	703	958
EC50T	150	2-4.5	110-140	30-50	670-1500	111	52	12	835	1115
EC60T	215	3-6	110-140	35-60	520-1300	113	62	14	904	1224
EC70T	275	4-9	110-140	45-75	520-1200	114	70	18	974	1339
EC80T	370	5-12	120-150	60-90	530-1000	115	80	23	1097	1527
EC90T	625	9-15	130-150	80-110	600-950	116	90	28	1213	1668
EC100T	800	12-19	150-170	100-120	-	118	100	34	1462	1982
EC120T	1200	15-24	150-170	120-140	-	121	120	40	1593	2218
EC135T	1500	17-28	150-170	140-160	-	122	135	45	1700	2340
EC140T	1800	20-33	150-170	130-180	400-800	120	140	51	1798	2418
EC150T	2200	25-40	150-170	150-200	450-800	120	150	57	1933	2568
EC155T	2600	30-45	160-180	180-220	530-800	122	155	66	2020	2675
EC165T	3000	35-55	160-180	220-270	540-800	123	165	81	2196	2886
EC180T	4200	45-70	160-180	250-320	550-800	-	180	96	2349	3114

\*Теглото на чука включва: тегло на самия чука, работен инструмент и адапторна плоча

	Service weight*	Carrier weight class	Operating pressure	Oil flow	Impact rate	Sound power level	Tool diameter	Max. hydraulic input	Height	
									without tool	with tool
	kg	t	bar	l/min	bpm	dB(A)	mm	kW	mm	mm
<b>EC40T</b>	95	1-3	110-130	15-35	560-1600	109	42	8	703	958
<b>EC50T</b>	150	2-4.5	110-140	30-50	670-1500	111	52	12	835	1115
<b>EC60T</b>	215	3-6	110-140	35-60	520-1300	113	62	14	904	1224
<b>EC70T</b>	275	4-9	110-140	45-75	520-1200	114	70	18	974	1339
<b>EC80T</b>	370	5-12	120-150	60-90	530-1000	115	80	23	1097	1527
<b>EC90T</b>	625	9-15	130-150	80-110	600-950	116	90	28	1213	1668
<b>EC100T</b>	800	12-19	150-170	100-120	-	118	100	34	1462	1982
<b>EC120T</b>	1200	15-24	150-170	120-140	-	121	120	40	1593	2218
<b>EC135T</b>	1500	17-28	150-170	140-160	-	122	135	45	1700	2340
<b>EC140T</b>	1800	20-33	150-170	130-180	400-800	120	140	51	1798	2418
<b>EC150T</b>	2200	25-40	150-170	150-200	450-800	120	150	57	1933	2568
<b>EC155T</b>	2600	30-45	160-180	180-220	530-800	122	155	66	2020	2675
<b>EC165T</b>	3000	35-55	160-180	220-270	540-800	123	165	81	2196	2886
<b>EC180T</b>	4200	45-70	160-180	250-320	550-800	-	180	96	2349	3114