

STG 45

Rebar Tier



sima

NEW

STG 45

Rebar Tier

ACCESSORIES INCLUDED

4 Wire coils included

Rugged plastic carry case

Fast Battery charger

2 High capacity batteries
Li-ion 18.5 V
5 Ah

TECHNICAL SPECIFICATIONS

Code	8534
Net weight	2,7 kg / 5,95 Lb
Gross weight	7,6 kg / 16,75 Lb
Tier dimensions	280 x 300 x 105
Carry case dimensions	11" x 11,81" x 4,13" 485 x 135 385
Wraps x tie	2 or 3
Min. Max. tying diameter	Ø6 - Ø45mm 2x #3 - 2x #6 rebar
Wire diameter	0,8 mm / 21 GA
Wire x coil	100 m / 330 ft approx.
Ties x coil	150 - 115 approx.
Ties x charge	up to 5.200 approx.
Battery	Li - Ion
Voltage	18,5 V.
Amps	5,0 Ah.
Charging time	60 min.



Easy-to-use & rugged digital display to set **wraps per tie** (2 or 3) and **tying torque** (1 to 10)



Battery life tester with LED lights



Heavy duty slide-in battery **18,5 V y 5 Ah** for longer operating time

EXCELLENCE AND RELIABILITY!



50 coils per pack
50 Packs per pallet
Shipping weight per
pack: **21 kg / 46.30 Lb**
Shipping weight per
pallet: **1085 kg /**
2,392 Lb approx.

FEATURES & BENEFITS



High Speed Operating

Up to five times faster than a hand made tie.

Less than a second per tie.



High Capacity Li-ion Battery (5 Ah)

Higher amperage to increase operational time:
up to 5200 ties per battery charge.



High-tech Electronics Inside

Features a new auto diagnosis system
on a digital display for the most common
possible failures.



Fast High Quality Ties

Perfect and tight ties.

Adjustable tying torque from 1 to 10.

Selection of 2 or 3 wraps per tie.



Quality Materials

Compact body made by last generation hard
impact ABS.

Ergonomic handle with rubber grip and shield
to protect the trigger.



Redesigned Jaws to Increase Endurance

New reengineered upper jaw, reinforced
and made by tempered steel for longer life.

Bigger jaws, tie rebar from 6 x 6 mm up
to 20 x 20 mm (#3 x #3 to #6 x #6 rebar)



Wire Coils Compatibility

Can use both, SIMA wire coils and other
brands.



optional: extension arm





Simma

www.simasa.com



Sima, S.A.

Pol. Juncaril, C/Albuñol, Parc. 250

18220 Albolote, Granada, Spain

Telf. +34 490 410

Fax: 34 466 645

