

MOTOMAN GP250

Handling & General Applications
with the GP-series







The 6-axis MOTOMAN GP250 is a versatile, high speed robot offering superior performance for a variety of applications, like material handling, machine and press tending.

Despite of providing a high payload of 250 kg and the wide motion range of 2710 mm, the MOTOMAN GP250 was designed with a width of 816 mm, therefore valuable floor space can be saved.

The vibration control system uses higher axis operation speed and speed reducer rigidity to allow fast acceleration of short movements. By reducing cycle times, this system realises high increases in productivity.

KEY BENEFITS

- Fast, flexible and powerful
- High payload: 250 kg
- Wide motion range: 2710 mm
- Maximum performance using minimal floor space



Mounting option: Floor
Protection class: IP54/67

Specifications GP250						
Axes	Maximum motion range [°]	Maximum speed [°/sec.]	Allowable moment [Nm]	Allowable moment of inertia [kg · m²]	Controlled axes	6
					Max. payload [kg]	250
S	±180	100	–	–	Repeatability [mm]	±0.2
L	+76/–60	90	–	–	Max. working range R [mm]	2710
U	+197/–77.89	97	–	–	Temperature [°C]	0 to +45
R	±360	120	1385	317	Humidity [%]	20 – 80
B	±125	120	1385	317	Weight [kg]	1345
T	±360	190	735	200	Power supply, average [KVA]	5.0