



Facts

- Easy replacement of wear parts
- Rotatable and very maneuverable
- Automatic wedge lubrication
- Multiple mounting options
- Lowest power-to-weight ratio on the market
- Use even under water

C20 J



C20 C



Specifications | Rock Splitters C20

Dimensions and weight	Vertical		Horizontal	
	C20 C		C20 J	
Length ¹ x Width x Height	1720 x 305 x 394 mm	68 x 12 x 16 in	2153 x 450 x 420 mm	85 x 18 x 17 in
Weight with N-wedge set ²	300 kg	660 lb	390 kg	860 lb
Carriers				
Recommended carrier weight ³	5 - 7 t		11000 - 15400 lb	
Recommended Brokk machines	Brokk 300 / 500 / 520D			
Hydraulic connection				
Connection pressure, min.	17,5 MPa		2540 psi	
Connection pressure, max.	22 MPa		3190 psi	
Oil flow, min. - max.	25 - 80 l/min		7 - 21 gal/min	
Rotary drive connection pressure, max.	22 MPa		3190 psi	
Rotary drive oil flow, max.	30 l/min		8 gal/min	
Operating pressure	50 MPa		7250 psi	
Wedge set				
Wedge set length N / L	640 / 840 mm		25.2 / 33.1 in	
Drillhole diameter	76 mm		3 in	
Drillhole depth N / L, min.	750 / 950 mm		29.5 / 37.4 in	
Splitting distance N / L	22 / 25 mm		0.9 / 1 in	
Theoretical splitting force N / L	1500 / 1800 t		3307000 - 3968000 lbf	
Consumables				
Darda Special Lubricant				

¹ Without wedge set ² Without mounting plate ³ Depending on carrier lifting capacity