Standard Equipment

- Single-phase 230V/50Hz motor Gearmotor in oil bath and high performance Poly-V transmission belt
- Electric safety limit switch
- Thermal-magnetic switch with IP 55 no-volt coil and IP 67 plug
- Paddle rotation reversing gear
- Grid with bag-splitting blade
- Extendable handles
- Lifting hooks
- Additional wheels

Applications

Powerful and versatile, it batches the most difficult products, both traditional and pre-mixed materials thanks to its high power, increased speed and the possibility to reverse the direction of rotation of the paddles.

115V/60Hz SPH 220V/60Hz SPH


MOTOR AVAILABLE

✓ Mix 120 Plus



Fast and homogeneous batching

Thanks to the forced-duty planetary mixing system the batching time is minimal: batching 80 litres of lean mortar takes about 40 seconds.



Outlet

(Mix 120 Plus seen from below) Optimized outlet for an easy discharge of the material.

		MIX 120 Plus
Drum capacity	I	120
Mixing performance	I	90
Drum diameter	mm	745
Max grain size	mm	8
Paddle speed	rpm	38
Electric motor power rate 230V/50Hz	kW	1.4
Running current	Α	9
SPL in operator's position	dB(A)	70
Machine weight (packing)	Kg	130 (139)
Dimensions w/l/h (packing)	mm	745/842/1277 (770/880/955)

