VENUS Mekano Range

Masonry Saw

The **VENUS Mekano** range is conceived to straight or 45° angle cut all kind of construction materials, particularly those of larger size, quickly, precisely and with the highest quality.

Models VENUS 125, 150 and 200 include a handwheel operated feed with a toothed belt transmission. It also includes a self-cleaning system of the sliding rails based on polishing felts and a folding guard in all models.

Model **VENUS 85** moves by operating a handle. As all **Mekano** machines, a 90 % of this range is manufactured with stainless materials.

The cutting head moves with the assistance of a bearings system mounted on an aluminium cart. These bearings are placed in 30° and 90° angles, ensuring a perfect straight or bevel cut, essential when cutting high value tiles and ceramics.

Their innovative upper bridge is also made in anodized reinforced aluminium. Fitting the cutting head is very easy and can use Ø300 mm (12") and Ø350 mm (14") blades.

It is the perfect machine to use at the job site and in marble or granite workshops, etc.

All the range models include a Ø350 mm blade as standard.

SIMA has available an especial **VENUS** model designed to performs cuts on polyurethane insulating panels. This model is delivered with a TCT blade and is fitted with the protection devices to ensure an easy, safe and fast cut.



FEATURES AND BENEFITS OF THE VENUS MEKANO RANGE



polyurethane insulating panels











an easy handling (standard)





	VENUS 85 MEKANO						
		1 - PH	IASE		3 - PHASE		3 - PHASE
Item code	0103002000	0103002001	0103002002	0103002003	0103002004	0103002005	0103002006
Motor voltage (V)	23	30	11	0		230 - 400	
Frequency (Hz) / In (pins)	50/3P 60/3P 50/3P 60/3P 50/4P 50/5P				60/4P		
Kw (Hp)		2,2	2 (3)		3 (4)		
Water tub capacity (L. / Gal.)				42 / 11			
Blade bore diameter (mm / in)				25,4/1"			
Max. blade diameter (mm / in)			30	00/350-12"/	4"		
Blade included (mm/in)				350 / 14"			
Max. cutting length (mm/in)			850/	h 20 - 33,4"/h	า 0,78"		
Max. cutting depth (mm/in)	75 / 100 - 3" / 4"						
Net weight (Kg. / lbs.)	84/185						
Packaging dimensions LxWxH (mm/in)	n) 1540 x 870 x 950 / 60,6" x 34,2" x 37,4"						
Folding legs + wheels				Yes			



	VENUS 125 MEKANO							
		1- PI	HASE		3 - PHASE		3 - PHASE	
Item code	0103003000	0103003001	0103003002	0103003003	0103003004	0103003005	0103003006	
Motor voltage (V)	23	30	11	0		230 - 400		
Frequency (Hz) / In (pins)	50/3P	60/3P	50/3P	60/3P	50/4P 50/5P 60/-			
Kw (Hp)		2,2	2 (3)		3 (4)			
Water tub capacity (L. / Gal.)				42 / 11				
Blade bore diameter (mm / in)		25,4/1"						
Max. blade diameter (mm / in)			30	300 / 350 - 12" / 14"				
Blade included (mm/in)				350 / 14"				
Max. cutting length (mm/in)			1250 /	h 20 - 49,21" /	/ h 0,78"			
Max. cutting depth (mm/in)	75 / 100 - 3" / 4"							
Net weight (Kg. / lbs.)	102,7 / 227							
Packaging dimensions LxWxH (mm/in)	n) 1960 x 870 x 950 / 77" x 34,2" x 37,4"							
Folding legs + wheels				Yes				



		1- PH	ΗA
Item code	0103004000	0103004001	01
Motor voltage (V)	23	30	
Frequency (Hz) / In (pins)	50/3P	60/3P	
Kw (Hp)		2,2	2 (3
Water tub capacity (L. / Gal.)			
Blade bore diameter (mm / in)			
Max. blade diameter (mm / in)			
Blade included (mm / in)			
Max. cutting length (mm/in)			
Max. cutting depth (mm/in)			
Net weight (Kg. / Ibs.)			
Packaging dimensions LxWxH (mm/in)			
Folding legs + wheels			

VENUS 150 MEKANO								
	1- PF	IASE	3 - PI	HASE	3 - PHASE			
0103004000	0103004001	0103004002	0103004003	0101004004	0101004005	0101004006		
23	30	11	0		230 - 400			
50/3P	60/3P	50/3P	60/3P	50/4P	50/5P	60/4P		
	2,2	(3)			3 (4)			
42 / 11								
25,4/1"								
300 / 350 - 12" / 14"								
350 / 14"								
1500 / h 20 - 59" / h 0,78"								
75 / 100 - 3" / 4"								
112,7 / 248								
2260 x 870 x 950 / 89" x 34,2" x 37,4"								
Yes								



Item code	(
Motor voltage (V)	
Frequency (Hz) / In (pins)	
Kw (Hp)	
Water tub capacity (L. / Gal.)	
Blade bore diameter (mm / in)	
Max. blade diameter (mm / in)	
Blade included (mm/in)	
Max. cutting length (mm/in)	
Max. cutting depth (mm/in)	
Net weight (Kg. / Ibs.)	
Packaging dimensions LxWxH (mm/in)	
Folding legs + wheels	

230 110 230 - 400 3P 60/3P 50/3P 60/3P 50/4P 50/5P 60/4P 2,2 (3) 3 (4) 42/11 25,4/1" 300/350 - 12"/14" 350/14" 2000/h 20 - 78"/h 0,78" 75/100 - 3"/4" 135/297 2800 x 870 x 950/110" x 32,4" x 37,4"								
50/3P 60/3P 50/3P 60/3P 50/4P 50/5P 60/4P 2,2 (3) 42/11 25,4/1" 300/350 - 12"/14" 350/14" 2000/h 20 - 78"/h 0,78" 75/100 - 3"/4"		1-P	HASE		3 - PI	HASE	3 - PHASE	
50/3P 60/3P 50/3P 60/3P 50/4P 50/5P 60/4P 2,2 (3) 42/11 25,4/1" 300/350 - 12"/14" 350/14" 2000/h 20 - 78"/h 0,78" 75/100 - 3"/4"		0103007000 010300700	0103007002	0103007003	0101007004	0101007005	0101007006	
2,2 (3) 3 (4) 42/11 25,4/1" 300/350 - 12"/14" 350/14" 2000/h 20 - 78"/h 0,78" 75/100 - 3"/4"		230	11	10		230 - 400		
42/11 25,4/1" 300/350 - 12"/14" 350/14" 2000/h 20 - 78"/h 0,78" 75/100 - 3"/4"		50/3P 60/3P	50/3P	60/3P	50/4P	50/5P	60/4P	
25.4/1" 300/350 - 12"/14" 350/14" 2000/h 20 - 78"/h 0,78" 75/100 - 3"/4"		2,	2 (3)			3 (4)		
300 / 350 - 12" / 14" 350 / 14" 2000 / h 20 - 78" / h 0,78" 75 / 100 - 3" / 4"				42 / 11				
350/14" 2000/h20-78"/h0,78" 75/100-3"/4"	25,4/1"							
2000 / h 20 - 78" / h 0,78" 75/100 - 3" / 4"		300 / 350 - 12" / 14"						
75/100 - 3"/4"		350 / 14"						
	2000 / h 20 - 78" / h 0,78"							
135 / 307		75/100 - 3"/4"						
123 / 531				135 / 297				
2800 x 870 x 950 / 110" x 32,4" x 37,4"			2800 x 870) x 950 / 110" x	32,4" x 37,4"			
Yes				Yes				

