



## NT 75/1 Me Ec H Z22

The TÜV tested NT 75/1 Me Ec H Z22 safety vacuum cleaner is a powerful, single motor wet and dry vacuum cleaner for explosive dust (hazard class zone 22) with continuous antistatic system.



### 1 Zone 22 + dust class M

- For combustible dusts in dust explosion classes, Zone 22 and health-endangering dusts, dust class M.

### 3 Variable speed control

- The brushless EC drive has a life expectancy of 5000 hours - ideal for continuous use.

### 2 Antistatic preparation

- All Kärcher safety vacuum cleaners feature a continuous antistatic system with conductive accessories.



## NT 75/1 Me Ec H Z22

- Brushless EC drive (5,000 h)
- Antistatic preparation
- Suitable for asbestos

### Technical data

|                               |                   |                 |
|-------------------------------|-------------------|-----------------|
| <b>Order no.</b>              | 1.667-239.0       |                 |
| <b>EAN code</b>               | 4039784538115     |                 |
| <b>Air flow rate</b>          | <b>l/s</b>        | 61              |
| <b>Vacuum</b>                 | <b>mbar / kPa</b> | 220 / 22        |
| <b>Container capacity</b>     | <b>l</b>          | 75              |
| <b>Max. rated input power</b> | <b>W</b>          | 1000            |
| <b>Standard nominal width</b> | 40                |                 |
| <b>Cable length</b>           | <b>m</b>          | 10              |
| <b>Sound pressure level</b>   | <b>dB(A)</b>      | 76              |
| <b>Weight</b>                 | <b>kg</b>         | 27.8            |
| <b>Dimensions (L × W × H)</b> | <b>mm</b>         | 640 × 540 × 925 |

### Equipment

|                                  |            |     |
|----------------------------------|------------|-----|
| <b>Suction hose</b>              | <b>m</b>   | 4   |
| <b>Filter bag</b>                | fleece     |     |
| <b>Wet and dry floor nozzle</b>  | <b>mm</b>  | 360 |
| <b>Crevice nozzle</b>            | ■          |     |
| <b>Antistatic preparation</b>    | ■          |     |
| <b>Stainless steel container</b> | ■          |     |
| <b>Flat pleated filter</b>       | Fibreglass |     |
| <b>Push handle</b>               | ■          |     |
| <b>Protection class</b>          | I          |     |
| <b>Steering roller stop</b>      | ■          |     |
| <b>Dust class</b>                | H          |     |

■ Included in the scope of supply.

# ACCESSORIES FOR NT 75/1 ME EC H Z22

## 1.667-239.0

**KÄRCHER**



|   |   | Order no.   | Quantity   | ID    | Length | Width  | Price | Description  |   |
|---|---|-------------|------------|-------|--------|--------|-------|--|---|
| <b>HEPA, dust class H filter</b>              |   |             |            |       |        |        |       |  |   |
| HEPA flat pleated filter                      | 1 | 6.904-364.0 | 1 piece(s) |       |        |        |       | HEPA surface filter - dust class H (H 14) - with glass-fibre layers increases filter capacity when vacuuming health-endangering and carcinogenic dust.               | ■ |
| <b>Bends, metal</b>                           |   |             |            |       |        |        |       |  |   |
| Bend, metal, non-interchangeable              | 2 | 4.036-032.0 | 1 piece(s) | ID 40 |        |        |       | Unmistakeable bend, chromium-plates and crooked, ID 40, with special fixation sleeves use with special safety vacuum cleaner for dust explosion classes B1.          | ■ |
| <b>Floor nozzles</b>                          |   |             |            |       |        |        |       |  |   |
| Wet and dry floor nozzle                      | 3 | 4.763-244.0 | 1 piece(s) | ID 40 |        | 360 mm |       | All-purpose plastic nozzle (DN 40) with 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0). Only for NT-80/1 B1 M + MS. | ■ |
| Wet and dry floor nozzle, non-interchangeable | 4 | 4.130-399.0 | 1 piece(s) | ID 40 |        | 450 mm |       | Aluminium floor nozzle, earthed, non-interchangeable, 450 mm, height adjustable. As a standard accessory for NT 80/1 B1 Ms and optional for NT 75/1 Me Ec H Z22.     | □ |
| <b>Crevice nozzles</b>                        |   |             |            |       |        |        |       |  |   |
| Crevice nozzle                                | 5 | 4.763-243.0 | 1 piece(s) | ID 40 | 290 mm |        |       | Plastic crevice tool (DN 35) with non-interchangeable screw connection for vacuuming in crevices and corners. Length: 290 mm.  | ■ |
| <b>Suction tubes, metal</b>                   |   |             |            |       |        |        |       |  |   |
| Suction tube, non-interchangeable             | 6 | 4.025-372.0 | 1 piece(s) | ID 40 | 1 m    |        |       | Non-interchangeable suction tube ID 40, 1.0 m, metal chromed, with special fixation on both sides.   | ■ |
| <b>All-purpose brushes</b>                    |   |             |            |       |        |        |       |  |   |
| Multi-purpose brush, non-interchangeable      | 7 | 4.763-242.0 | 1 piece(s) | ID 40 | 120 mm |        |       | All-purpose brush with natural bristles (cow hair) Bristles: 120 x 45 mm. Only for NT 801 B1 M, B1 MS and NT 80/1 B1 M & B1 MS.                                      | □ |

■ Included in the scope of supply. □ Available accessories.

# ACCESSORIES FOR NT 75/1 ME EC H Z22

## 1.667-239.0



|  |   | Order no.   | Quantity   | ID | Length / width | Price | Description  |   |
|--|---|-------------|------------|----|----------------|-------|--|---|
| <b>Filters and waste disposal bags</b> |   |             |            |    |                |       |  |   |
| Safety filter bags                     | 1 | 6.904-420.0 | 5 piece(s) |    |                |       | For dust-free/low-dust emptying in conjunction with the 4.070-930.0 container, with dust disposal bag, electrically conductive. Checked and approved for dust class H. | ■ |

Included in the scope of supply.
  Available accessories.