Always the right tool

SLTflex – for the awkward areas!

Feel the efficiency compared to conventional lamellar flap discs or fibre discs.

Ideal for:

- machining of fillet welds
- deburring
- fettling
- fine finishing
- rust removal

SLTflex Series

Using a high quality coated abrasive (zirconia with a coating of active grinding additives)

High Performance

SLTfex – for radii and fillet weldings

Ordering example: A272910004018



Packing unit:
10 pcs. per type
$v_{max.}$: 80 m/s
ZKS – Zirconia Alum. Oxide with special coating containing active grinding additives
ZK – Zirconia Alum. Oxide

Series

Description	Grits	D mm	Thread	n max (1/min)	Product-Number	recommended for									
SLTFLEX 100	ZKS 40	100	M10	15.300	A272910004018	1	2	3	4	5	6	7		■	
SLTFLEX 100	ZKS 60	100	M10	15.300	A272910006018	1	2	3	4	5	6	7		■	
SLTFLEX 100	ZKS 80	100	M10	15.300	A272910008018	1	2	3	4	5	6	7		■	
SLTFLEX 115	ZKS 40	115	M14	13.300	A272711504018	1	2	3	4	5	6	7		■	
SLTFLEX 115	ZKS 40	115	5/8"	13.300	A272811504018	1	2	3	4	5	6	7		■	NEW
SLTFLEX 115	ZKS 60	115	M14	13.300	A272711506018	1	2	3	4	5	6	7		■	
SLTFLEX 115	ZKS 60	115	5/8"	13.300	A272811506018	1	2	3	4	5	6	7		■	NEW
SLTFLEX 115	ZK 80	115	M14	13.300	A272711508018	1	2	3	4	5	6	7		■	
SLTFLEX 115	ZK 80	115	5/8"	13.300	A272811508018	1	2	3	4	5	6	7		■	NEW
SLTFLEX 115	ZK 120	115	M14	13.300	A272711512018	1	2	3	4	5	6	7		■	
SLTFLEX 115	ZK 120	115	5/8"	13.300	A272811512018	1	2	3	4	5	6	7		■	NEW
SLTFLEX 125	ZKS 40	125	M14	12.200	A272712504018	1	2	3	4	5	6	7		■	
SLTFLEX 125	ZKS 40	125	5/8"	12.200	A272812504018	1	2	3	4	5	6	7		■	NEW
SLTFLEX 125	ZKS 60	125	M14	12.200	A272712506018	1	2	3	4	5	6	7		■	
SLTFLEX 125	ZKS 60	125	5/8"	12.200	A272812506018	1	2	3	4	5	6	7		■	NEW
SLTFLEX 125	ZK 80	125	M14	12.200	A272712508018	1	2	3	4	5	6	7		■	
SLTFLEX 125	ZK 80	125	5/8"	12.200	A272812508018	1	2	3	4	5	6	7		■	NEW
SLTFLEX 125	ZK 120	125	M14	12.200	A272712512018	1	2	3	4	5	6	7		■	
SLTFLEX 125	ZK 120	125	5/8"	12.200	A272812512018	1	2	3	4	5	6	7		■	NEW
SLTFLEX 178	ZKS 40	178	M14	8.500	A272917804018	1	2	3	4	5	6	7		■	
SLTFLEX 178	ZKS 60	178	M14	8.500	A272917806018	1	2	3	4	5	6	7		■	
SLTFLEX 178	ZKS 80	178	M14	8.500	A272917808018	1	2	3	4	5	6	7		■	

Properties:

- high flexibility due to elongated flaps (no disturbing backing plate)
- simple tool change (backing plate / pad and mounting nut no longer required)
- extreme tool life

71.1%