


**High Performance**  
**V2 Power INOX to work on stainless steel**  
*Ordering example A27441150401445*




**Packing unit:** 10 pcs. per type  
 $v_{max}$ : 80 m/s  
**Z POWER** – Abrasive cloth using Zirconia Alum. Oxide with special coating containing active grinding additives

Description	Grits	D mm	H mm	n max. (U/min)	Product-Number	recommended for
V2 POWER 115	Z Power 40	115	22,23	13.300	A27441150401445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 115	Z Power 60	115	22,23	13.300	A27441150601445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	Z Power 40	125	22,23	12.200	A27441250401445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	Z Power 60	125	22,23	12.200	A27441250601445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	Z Power 40	178	22,23	8.500	A27441780401445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	Z Power 60	178	22,23	8.500	A27441780601445	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

**Properties:**  
 • no glazing or heat generation  
 • equally efficient for both edge and surface applications  
 • iron-sulphur-chlorine free

**High Performance**  
**V2 Power Heavy Duty for roughest application**  
*Ordering example A27441150401450*




**Packing unit:** 10 pcs. per type  
 $v_{max}$ : 80 m/s  
**Ceramic** – ceramic grain

Description	Grits	D mm	H mm	n max. (U/min)	Product-Number	recommended for
V2 POWER 115	Ceramic 40	115	22,23	13.300	A27441150401450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 115	Ceramic 60	115	22,23	13.300	A27441150601450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	Ceramic 40	125	22,23	12.200	A27441250401450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	Ceramic 60	125	22,23	12.200	A27441250601450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	Ceramic 40	178	22,23	8.500	A27441780401450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	Ceramic 60	178	22,23	8.500	A27441780601450	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 230	Ceramic 40	230	22,23	6.800	A27442300401428	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

**Properties:**  
 • particularly robust for edge grinding, on heat treated steels, surface scale or coated surfaces  
 • iron-sulphur-chlorine free  
 • >1000 W opt.



**High Performance**  
**V2 Power Steel for universal application on steel and aluminium**  
*Ordering example A27441000401465*




**Packing unit:** 10 pcs. per type  
 $v_{max}$ : 80 m/s  
**ZK** – Abrasive cloth with Zirconia Alum. Oxide  
**ZKS** – Zirconia Alum. Oxide with special coating containing active grinding additives

Description	Grits	D mm	H mm	n max. (U/min)	Product-Number	recommended for
V2 POWER 100	ZK 40	100	16	15.300	A27441000401465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 100	ZK 60	100	16	15.300	A2744100601465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 115	ZK 40	115	22,23	13.300	A27441150401465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 115	ZK 60	115	22,23	13.300	A27441150601465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	ZK 40	125	22,23	12.200	A27441250401465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 125	ZK 60	125	22,23	12.200	A27441250601465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	ZK 40	178	22,23	8.500	A27441780401465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 178	ZK 60	178	22,23	8.500	A27441780601465	① ② ③ ④ ⑤ ⑥ ⑦ ⑧
V2 POWER 230	ZKS 40	230	22,23	6.800	A27442300401418	① ② ③ ④ ⑤ ⑥ ⑦ ⑧

**Properties:**  
 • tough grain with a high degree of resistance to pressure

**High Performance**  
**V2 POWER ALU**  
*Ordering example A27441150401434*



**Packing unit:** 10 pcs. per type  
 $v_{max}$ : 80 m/s  
**SIC** – Silicon carbide

Description	Grits	D mm	H mm	n max. (U/min)	Product-Number	recommended for
V2 POWER 115	SIC 36	115	22,23	13.300	A27441150361434	① ② ③ ④
V2 POWER 115	SIC 40	115	22,23	13.300	A27441150401434	① ② ③ ④
V2 POWER 125	SIC 36	125	22,23	12.200	A27441250361434	① ② ③ ④
V2 POWER 125	SIC 40	125	22,23	12.200	A27441250401434	① ② ③ ④
V2 POWER 178	SIC 24	178	22,23	8.500	A27441780241434	① ② ③ ④
V2 POWER 178	SIC 36	178	22,23	8.500	A27441780361434	① ② ③ ④

**Properties:**  
 • silicon carbide (SIC) ideally suited for preparation and finishing of weld seams with various aluminium alloys  
 • Silicon carbide (SIC) ideally suited for the machining of contemporary workpiece materials such as CFR or GRP

