

# The EstrichBoy

The "original" over 50 years!




**STAGE V**  
ready to work

**For conventional semi-dry floor screed with different binder additives such as cement, anhydrite, etc.**



The EstrichBoy from Putzmeister – advancement and unrivalled configuration options.

The EstrichBoy is convincing up to the smallest detail.

- More drive power thanks to the 36.4 kW Deutz engine – "Stage V" emission category
- Reliable, robust and easy to operate
- High delivery rate, improved efficiency
- Extra Power (as option):  BluePower
- Of lasting value and economical thanks to the high resale value
- Top class service with wide dealer service network
- Training for users and engineers in our Academy



**BRINKMANN**



Environmentally friendly Deutz diesel engine with Stage V emission category. BluePower (optional) for maximum output – allows reduced engine speeds for fuel economy.



Everything in view due to the new ergonomic control panel - now with robust keypad.



Bag deposit – new (optional)



Toolbox (optional)



Lifting eye (optional)



Water dosing (optional)

## Further benefits:

- Technology „made in Germany“
- Optimized accessibility and ground clearance
- Low maintenance and wear-resistant
- Flexible application possibilities
- Choose "your" machine with a wide variety of equipment options
- High delivery rate, improved efficiency

## Technical data

Mixer drum	260 l, 200 l useful capacity
Delivery range*	180 m horizontally, 90 m vertically
Output (theo.)*	3,8–5 m³/h
Delivery pressure	8 bar
Compressor	4,4 m³/min
Engine	Diesel, 3-cylinder Deutz with turbocharging, 36.4 kW (emission category Stage V)
Tank capacity	70 l
Weight	1715 kg / 1840 kg (B) / 1900 kg (BS)
Length × width × height	4790 × 1560 × 1640 mm
	5020 × 1560 × 2515 mm (B)
	5020 × 1560 × 2515 mm (BS)
Filling height	900 mm (B + BS 400 mm)
Chassis	braked, 80 km/h (100 km/h optional)
Maximum grain size	16 mm

Equipment		DC 450	B	BS
Series	Straight overrun device	■	■	■
	Manual lid	■	■	■
	Central lubrication system	■	■	■
	Vessel outlet, front	■	■	■
	Impact protection bars, one side	■	■	■
	Car coupling	■	■	■
Optional	Working light	■	■	■
	BluePower	■	■	■
	Lid automatic	■	■	■
	Lid manual, longitudinal	■	-	-
	High pressure cleaner	-	■	■
	Vessel outlet, center	■	■	■
	Lifting eye	■	■	■
	Customer labelling	■	■	■
	Light holder 24 V	■	■	■
	Truck coupling	■	■	■
	Mixing time adjustment	■	■	■
	Location system (GPS)		on request	
	Bag deposit	■	■	■
	Protective plate for feeder	-	■	■
	Special canopy paint in RAL colours	■	■	■
	Support feet	-	■	■
	Conversion to 100 km/h	■	■	■
	Wear plates at the dome	■	■	■
	Wear plates Hardox 6 mm	■	■	■
	Wear plates Hardox 8 mm	■	■	■
Wear plates front end, front	■	■	■	
Wear plates front end, center	■	■	■	
Wear plates, plastic	■	■	■	
Water dosing	■	■	■	
Toolbox	■	■	■	

\* The data is based on experience and depends on the material properties.

■ Series ■ Optional

BRINKMANN  
 A brand of the Putzmeister Group  
 Max-Eyth-Straße 10 · 72631 Aichtal  
 Tel. +49 (7127) 599-0 · Fax +49 (7127) 599-743  
 info@estrichboy.de · www.estrichboy.de

