



### NT 35/1 Tact Bs

Handy, highly absorbent one-engined wet/dry vacuum cleaner with innovative, patented, auto filter clean system - TACT - and with a container volume of 35 I for all applications in the bakery and confectionery craft. The special PES flat pleated filter system allows changing between wet and dry vacuuming without filter change. The unit will be delivered without accessories. The NT 35/1 Tact Bs is serially equipped with an antistatic system up to the suction hose connection, accessory holder for the storage of baking oven nozzle or the baker's kit (both special accessories) with heat resistant container and rubber power cord.

#### 1 The vacuum cleaner for bakeries

- The plastic container is acid, lye and heat resistant.
- The optional accessory kits were developed specially for use in bakeries.

#### 2 Heat-resistant PES flat pleated filter

The machine has a heat-resistant PES flat pleated filter, dust class M

 ideal for effortless removal of dust and dirt in bakeries.

### **TECHNICAL DATA AND EQUIPMENT**





#### NT 35/1 Tact Bs

- Antistatic preparation
- Tact automatic filter cleaning system
   Accessory holder for oven nozzle

Technical data		
Order no.		1.184-700.0
EAN code		4039784722668
Air flow rate	I/s	61
Vacuum	mbar / kPa	230 / 23
Container capacity	1	35
Max. rated input power	W	1380
Standard nominal width		35
Cable length	m	7.5
Sound pressure level	dB(A)	63
Weight	kg	12.8
Dimensions (L × W × H)	mm	580 × 375 × 517

Equipment		
Flat pleated filter		PES
Automatic switch-off at max. filling quantity		•
Antistatic preparation		I .
Container material		plastic
Eco filter system		I .
Heat-resistant plastic container		I
Filter cleaning		Tact filter cleaning system
Protection class		
Steering roller stop		1
Maintenance-free suction turbines	piece(s)	1
■ Included in the scope of supply.		

























						_			_
		Order no.	Quantity	ID	Length	Width	Price	Description	
Flat pleated filter, PES	<u> </u>		,						Ė
Flat pleated filter, PES	1	6.904-360.0	1 piece(s)					Flat pleated filter (PES) - BIA-C dust class M: rotproof polyester fleece, ideal for wet use and abrasives. Standard for NT 35/1 Eco BS and NT 55/1 Eco BS.	
Nozzle kits									
Nozzle kit	2	2.860-116.0	1 piece(s)	ID 35				Nozzle kit for all NT vacuum cleaners with DN 35 accessories includes crevice tool, upholstery tool, round brush (x3)	
Fabric filter									
Membrane filter	3	6.904-212.0	1 piece(s)					Polyester needle fleece membrane/fabric filter, washable u to 40°C, suitable for all NT 361 Eco to NT 611 Eco versions as an alternative to a filter bag.	
Wet filter bag		1				,		,	ļ,
Wet filter bag	4	6.904-171.0	5 piece(s)					Approved for dust class L, general cleaning, wet and dry, tear-resistant.	[
Fleece filter bags (three-ply)		1				,			
Adv fleece filter bags	5	6.904-351.0	5 piece(s)					3-ply tear-resistant fleece filter bags (dust class M). For dry pick up, suitable for the following models: NT 361 Eco, Eco TE, TE-A and NT 361 Eco M, NT 35/1 Eco, Eco Te, Eco M. Contents: x5	1
Bends, stainless steel		'	<u>'</u>						Ė
Bend, stainless steel, ID 35	6	6.903-141.0	1 piece(s)	ID 35				Stainless steel and crooked, ID 35	[
Bend, stainless steel, ID 40	7	6.902-079.0	1 piece(s)	ID 40				Stainless steel and crooked, ID 40	[
Bend, plastic									
Plastic bend	8	5.031-718.0	1 piece(s)	ID 35				Plastic bend (DN 35) with C-35 clip system. For all industria single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	
Bend, plastic, electrically conductive	9	5.031-939.0	1 piece(s)	ID 35				Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	[
Bend, plastic	10	6.902-009.0	1 piece(s)	ID 35				Plastic, ID 35.	[
Bends, metal					<u>'</u>				
Bend, metal	11	6.900-519.0	1 piece(s)	ID 35				Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0; C 35-DN 35, plastic, el.).	[
	12	6.900-276.0	1 piece(s)	ID 40				Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0; C 40-DN 40, plastic, el.).	[
All-purpose brushes			,	,					Ţ
All-purpose brush	13	6.903-863.0	1 piece(s)	ID 35	120 mm			Natural bristles (ox hair), bristle element 120 x 45 mm.	[
Floor nozzles									
Wet and dry floor nozzle	14	6.906-512.0	1 piece(s)	ID 35		300 mm		All-purpose plastic nozzle (DN 35) with 300 mm working width. With side rollers, brush strips (6.903-278.0) and squeegees (6.903-277.0). Only for NT vacuum cleaners.	[

<sup>■</sup> Included in the scope of supply. 

□ Available accessories.





























	1							T	$\top$
		Order no.	Quantity	ID	Length	Width	Price	Description	
Multi-purpose nozzle, wet/dry	15	6.903-018.0	1 piece(s)	ID 40		370 mm		All-purpose aluminium nozzle with 370 mm working width.	t
								With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	
	16	6.906-383.0	1 piece(s)	ID 40		450 mm		All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	
	17	6.906-384.0	1 piece(s)	ID 35		370 mm		All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	
DN 40 wet/dry floor nozzle	18	6.907-408.0	1 piece(s)	ID 40		360 mm		Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0).	
Car cleaning nozzles	1	ı		1		ı			
Car nozzle	19	6.906-108.0	1 piece(s)	ID 35		90 mm		Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.	
Oven nozzles			<u>'</u>	<u>'</u>					Ţ
Oven nozzle	20	4.130-104.0	1 piece(s)	ID 35		350 mm		Aluminium, for cleaning ovens with squeegee 6.900-517.0 and support squeegee 6.900-518.0, each 2x.	
	21	4.130-173.0	1 piece(s)	ID 35		350 mm		For cleaning baking ovens with scratch bar.	[
Crevice nozzles	۱ ۵۵		1	Lipios	Lava	ı		later to the temperature of the	Т
Crevice nozzle	22	6.900-385.0	1 piece(s)	ID 35	210 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	[
	23	6.900-922.0	1 piece(s)	ID 35	500 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	
	24	6.903-033.0	1 piece(s)	ID 40	290 mm			Plastic crevice tool (DN 40) for vacuuming in crevices and corners. Length: 290 mm.	
	25	6.905-817.0	1 piece(s)	ID 40	400 mm			Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	
	26	6.906-240.0	1 piece(s)	ID 35	250 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 250 mm.	
Rubber suction tools, nose 45°									Ţ
Rubber suction tool, nose 45°	27	6.902-104.0	1 piece(s)	ID 35	220 mm			45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	2 [
Radiator brushes		,					,		
Heater brush	28	6.903-034.0	1 piece(s)	ID 35				Radiator brush is suitable for crevice tool 6.900-385.0 or 6.905-240.0.	
Combi-nozzles, dry									Ť
Combi-nozzle, dry	29	6.906-511.0	1 piece(s)	ID 35		270 mm		Combination floor tool with changeover function, plastic (272 mm). With stainless steel base plate, thread catcher 6.905-417.0 and DN 35 connection.	
Pipe dusting nozzles			_						
Pipe brush 35/100	30	6.903-035.0	1 piece(s)	ID 35				Plastic, pipe diameter 100 mm	-
Pipe brush 35/200	31	6.903-036.0	1 piece(s)	ID 35				Plastic, pipe diameter 200 mm	
Suction brushes		1	1			1			
Suction brush	32	6.903-862.0	1 piece(s)	ID 35		70 mm		Rotatable suction brush (DN 35) with natural bristles (cow hair). Bristle size 70x45 mm. Only CV and NT vacuum clean	- [
■ Included in the scene of sup		□ Available as	<u> </u>					ers.	

<sup>■</sup> Included in the scope of supply. 

□ Available accessories.































		I	T	1	1		1	
		Order no.	Quantity	ID	Length	Width	Price	Description
Suction tubes, stainless steel							<u> </u>	
Suction tube	33	6.902-081.0	1 piece(s)	ID 40	0.5 m			Stainless steel suction tube (DN 40, 0.5 m) only suitable for
								N1 vacuum cleaners.
	34	6.906-531.0	1 piece(s)	ID 40	1 m			Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.
Suction tubes, plastic	I				1			W vaccom cicaners.
Suction tube	35	6.900-384.0	1 piece(s)	ID 35	0.5 m			Plastic suction tube (DN 35, 1x0.5 m) only suitable for BV
								and T vacuum cleaners.
Suction tubes, metal		1	1	1	1			la company and a second
Suction tube	36	6.900-514.0	1 piece(s)	ID 35	0.5 m			Chromium-plated metal suction tube (DN 35, 1x0.5 m),
								standard for virtually all single-motor industrial NT vacuum   Cleaners.
	37	6.900-275.0	1 piece(s)	ID 40	0.55 m			The suction tube (NW 40, 1 x 0.55 m) made from
			, , , ,					chrome-plated metal is standard in almost all commercial
								vacuum cleaners with twin motor. Optional for commercial
								single motor NT vacuum cleaner with suction hose NW 40.
Repair kits	1 20	1 2 6 20 6 8 2 0	1 minon(s)	Liplac		1	1	Repair set (C35) includes threaded hose adapters (without
Repair kit, C 35	38	2.639-682.0	1 piece(s)	ID 35				bayonet adapter) for industrial NT vacuum cleaners with clip [
								system.
Suction hoses (clip system)					·			
Suction hose	39	6.906-241.0	1 piece(s)	35	4 m			4 m suction hose without bend and adapter. With bayonet
								at vacuum end and C 35 clip connection at accessory end.
	40	6.906-275.0	1 piece(s)	35	2.5 m			2.5 m electrically conductive suction hose without bend and
								adapter with bayonet at vacuum end and C 35 clip connection at accessory end.
	41	6.906-500.0	1 piece(s)	35	4 m			4 m electrically conductive suction hose without bend and
								adapter with bayonet at vacuum end and C 35 clip connec-
								tion at accessory end.
	42	6.906-321.0	1 piece(s)	40	4 m			4 m suction hose with bayonet and C 40 clip connection.
	43	6.906-546.0	1 piece(s)	40	4 m			Without bend and adapter.  Electrically conductive, 4 m suction hose with bayonet and C
	43	0.500 540.0	1 piece(s)	40	4 111			40 clip connection. Without bend and adapter.
	44	6.906-877.0	1 piece(s)	40	10 m			Suction hose with bayonet coupling, electrically conductive.
Suction hose (clip system), C 35,	45	6.906-242.0	1 piece(s)	C- 35	10 m			Electrically conductive 10 m suction hose with bayonet
10 m								adaptor and C 40 clip adaptor. Without manifold or connec-
Suction hoses complete								tion bushing.
Suction hose, complete	46	4.440-287.0	1 piece(s)	ID 35	4 m	1		Standard, 4.0m, ID 35
Suction hose, complete, 120°C	47	4.440-339.0	1 piece(s)	ID 35	2.5 m			Temperature-resistant to 120 °C.
Complete suction hoses (clip system		4.440 333.0	1 piece(s)	18 33	2.5 111		1	remperatore resistant to 120 c.
Suction hose	48	4.440-626.0	1 piece(s)	ID 35	2.5 m			2.5 m standard suction hose with bend, bayonet at vacuum
			, , , ,					end and C 35 clip connection at accessory end. Without
								PDFC module. Standard for NT 2//1/Me Advance und NT
			4 . ()	10.05	0.5			48/1.
Suction hose, electrically conductive	49	4.440-653.0	1 piece(s)	ID 35	2.5 m			2.5 m electrically conductive suction hose with bend, bayonet at vacuum end and C 35 clip connection at accessory
UVC								end. Without module.
Special hoses				•				
Special suction hose, heat-resistant	50	4.440-731.0	1 piece(s)	ID 35	2.5 m			Special suction hose, DN 35, 2.5 m, for e.g. oven cleaning,
								temperature-resistant to 140°C, plastic - metal.





















		1	1	1		1	1		$\overline{}$
		Order no.	Quantity	ID	Length	Width	Price	Description	
Extension hoses (clip system)		ı							T
Extension hose	51	6.906-344.0	1 piece(s)	ID 40	2.5 m			2.5 m electrically non-conductive standard extension hose for all C-40 hoses with clip system.	
Connection adapter C ID (clip to con	e), ele	ctrically conduct	tive						
Connection adapter C DN 35	52	5.407-112.0	1 piece(s)	ID 35				C 35 hose connector for DN 35 accessory, electrically conductive.	
Connection adapter C DN 40	53	5.407-109.0	1 piece(s)	ID 40				Electrically conductive adapter (C 40) with DN 35 connection for connection DN 35	Г
								tion for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	
Expansion pieces (tube -> nozzle)							·		
Adapter ID 35 - 40 (tube -> noz-zle)	54	6.902-084.0	1 piece(s)	ID 35				From DN 35 to DN 40: Plastic adapter (electrically non-conductive). Suitable for NT vacuum cleaners.	Г
Reducing sleeves									
Reducer	55	5.407-108.0	1 piece(s)	ID 40				Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	
Reducers (tube -> nozzle)									
Reducer	56	6.902-017.0	1 piece(s)	ID 40				Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.	1 [
Reducer from ID 35 to ID 32	57	6.902-072.0	1 piece(s)	ID 35				Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	
Reduction/expansion adapter kit		L	_L	L			1	combination with madding in vaccom deciners.	
Set of reducers / adapter sleeves	58	2.860-117.0	1 piece(s)					DN 40/35, DN 35/32 (tube -> nozzle), plastic.	
Target-group-specific accessory kit	s for v	acuum cleaners	•	•	•	•			
Oven kit	59	2.640-341.0		ID 35				Accessory kit for vacuuming and cleaning ovens in bakeries, cake shops, etc.	
Bakery kit, electrically conductive	60	2.640-436.0		ID 40				Accessory kit for vacuuming and cleaning bakeries, equipment, shelves, etc. Ideal for bakeries, cake shops, etc.	
Flat pleated filter, PTFE									
Flat pleated filter, PTFE	61	6.907-455.0	1 piece(s)					Polyester fleece with PTFE coating for single-motor Tact and Ap vacuum cleaners, dust class M. Particularly suitable for very adhesive materials.	

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\square$  Available accessories.





		Order no.	Length	Colour	Quanti- ty	Price	Description
Miscellaneous							
Extension cable	1	6.647-022.0	20 m		1 piece(s)		Extension cable, 20 m, 3x1.5 mm². With splash-proof earthing pin plug, strain relief and anti-kink sleeve.

<sup>■</sup> Included in the scope of supply. 

□ Available accessories.







					Length			
		Order no.	Quantity	ID	/ width	Price	Description	
Other nozzles								
Surface nozzle, aluminium	1	4.130-415.0	1 piece(s)	ID 61	200 mm		Flat surface nozzle cpl. DN 51, 200 mm, aluminium with brush and stainless steel bumper	
Crevice tools								
Crevice nozzle, plastic	2	6.900-222.0	1 piece(s)	ID 61	370 × 64 mm		Grout nozzle, plastic, 370 mm	

<sup>■</sup> Included in the scope of supply. 

Available accessories.