

## **CUP BRUSHES**



Appearance can vary from picture depending on variant.





## CUP BRUSHES, KNOTTED WIRE

Knotted cup brush, high-end quality, for use on angle grinders

- High-performance wire developed by Osborn
- Particularly cost-effective
- Long life, high tensile strength, high breaking strain and short set-up times
- Special feature: individual knot ends are slightly open, so that the wire tips are in use immediately and directly
- Higher removal rate, aggressive cleaning performance

Applications: Paint/rust removal, deburring, descaling, removal of slag, silicate residues and blue discolouration, cleaning of fill layers and surfaces in the oil and gas industries

|     |    |         |          |   | ■ Osborn steel / 0.50 ■ |           | Osborn steel / 0.80 m |           |           |           |
|-----|----|---------|----------|---|-------------------------|-----------|-----------------------|-----------|-----------|-----------|
| 0   | Ť  | G       | Max. RPM | 8 | Order no.               | € per pcs | Order no.             | € per pcs | Order no. | € per pcs |
| 90  | 32 | M14x2.0 | 7500     | 6 | 9906-033 125            |           |                       |           |           |           |
| 90  | 32 | 58*     | 7500     | 6 | 9906-033 126            |           |                       |           |           |           |
| 150 | 45 | 58"     | 6000     | 1 |                         |           | 9906-033 021          |           |           |           |
| 150 | 45 | 58*     | 6000     | 1 | 9906-033 030            |           |                       |           |           |           |
| 150 | 45 | M14x2.0 | 6000     | 1 | 9906-033 031 *          |           |                       |           |           |           |

<sup>\*</sup> Two rows



Appearance can vary from picture depending on variant





## CUP BRUSHES, KNOTTED WIRE

Knotted cup brush, craftsman quality, for use on angle grinders

- Osborn bestseller in the DIY sector
- Good cleaning performance
- Best price/performance ratio
- Easy cleaning of larger areas

Applications: Paint/rust removal, removal of slag



Available in practical PET packaging with Euro-standard hole.



|     | T  | G       | Max. RPM | a  | ■ Steel / 0.35 ■ |           | ■ Steel / 0.50 ■ |           |           |           |
|-----|----|---------|----------|----|------------------|-----------|------------------|-----------|-----------|-----------|
| 0   |    |         |          |    | Order no.        | € per pcs | Order no.        | € per pcs | Order no. | € per pcs |
| 65  | 20 | M14x2.0 | 12500    | 10 | 2008-608 131     |           | 2008-608 151     |           |           |           |
| 75  | 27 | M14x2.0 | 1000     | 10 |                  |           | 2008-608 152     |           |           |           |
| 80  | 22 | M14x2.0 | 8500     | 10 |                  |           | 2008-608 153     |           |           |           |
| 100 | 22 | M14x2.0 | 8500     | 5  |                  |           | 2008-608 154     |           |           |           |